

SPECIFICATION SHEET

PRODUCT # : CL-342B-AB

•Step Lights

•Cast Brass



Fixture Specifications:

Housing: Corrosion Resistant Cast Brass.
Face Plate: Diecast solid brass, fitted to housing with silicone "O" ring gasket.
Finish: **AB- Antique Bronze.** Natural toning process. AB finish will vary due to artistic process.
Lens: Frosted and heat resistant flat glass.
Socket: Top grade fixed T5 wedge socket.
Lamp: 12V, T5 wedge, 18w max. L-WDG-921 (18w) standard. See below for available LED lamp.
Mounting: Surface mounted including mounting plate.

Wiring: Fixture is prewired with a 3-ft 18-2 SPT1-W direct burial cord. Wire connector available separately. Universal connector CX-839 or gel filled wire nut CX-854 may be ordered to Corona Lighting.
Gasket: Silicone "O" ring seals face plate to housing providing weather tight protection
Electrical Notes: A remote 12V transformer required, may be ordered to Corona Lighting separately. Voltage range for 12V wedge lamp is 11V-12.5V.
Warranty: Limited lifetime warranty on fixture against manufacturer's defects.



Twist To Lock Function
Tool Free relamping.



Available T5 Wedge LED Lamp

LAMP NUMBER	WATTS	BEAM		COLOR & TEMP.	ORDER CODE
		SPREAD	LUMEN		
L-EDWDG1W-WW	1	180°	60	WW 3000K	WDG-1W-WW

Available T5 Incadescent Wedge Lamps

LAMP NUMBER	WATTS	LUMEN	COLOR & TEMP.	ORDER CODE
L-WDG-904	6	50	WW 2700K	904
L-WDG-906	8	75	WW 2700K	906
L-WDG-912	12	150	WW 2700K	912
L-WDG-921	18	265	WW 2700K	921

JOB INFORMATION

TYPE: _____ DATE: _____
 JOB NAME & ADDRESS: _____
 PRODUCT #: _____
 TOTAL QUANTITY: _____
 LAMP TYPE & WATTAGE: _____
 TRANSFORMER: _____
 CONTRACTOR: _____
 SPECIFIER: _____