

3" Canless Koto™ IC New Construction Frame



IC Rated for direct contact with insulation. Easy-to-remove driver included on frame. To be used with Canless Koto™ LED Modules.


Features

- Must be used with Canless Koto™ LED Modules
- IC Rated for direct contact with insulation
- Easy-to-removed driver included
- Driver specified for 120V (Triac/ELV) or 120/277V (0-10V/Triac/ELV)

Specifications

Wattage	11.9W
Lumens	950 lm
Voltage	120/277V or 120V
Dimmable	Triac/ELV, 0-10V/Triac/ELV

Dimensions



Technical Details

Construction: IC rated for direct contact with insulation. For use in IC and Non-IC conditions.

Installation: High strength hanger bars can easily be nailed to joists. Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Hanger Bars: Pre-Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

Electrical: Driver is rated for 120V or 120/277V input. High Efficiency driver with a power factor > 0.95.

Dimmability: Option ELV/TRIAC dimming or 3 in 1 dimming: Triac, ELV and 0-10V dimming can be specified.

Product Numbers

Item	Description	Lumens	Watts	Voltage	Dimming
E3KCL10IC		950 lm	11.9W	120V	Triac/ELV
E3KCL10IC-EM1	90 min. Emergency Battery Backup	950 lm	11.9W	120V	Triac/ELV
E3KCL10ICDX		950 lm	11.9W	120/277V	0-10V/Triac/ELV
E3KCL10ICDX-EM1	90 min. Emergency Battery Backup	950 lm	11.9W	120/277V	0-10V/Triac/ELV

Product Number Builder Example: E3KCL10IC

3" Canless Koto™ IC New Construction Frame

Dimming - Voltage

Optional

E3KCL10IC

Triac/ELV - 120V

Standard

DX 0-10V/Triac/ELV -120/277V

-EM1 EM Battery Backup