

4" New Construction IC Airtight Housing w/Driver - E4LC08



Single Wall IC Airtight housing for high-end residential and light commercial, 850 lumens.

Features

- UL Listed for direct contact with insulation.
- Optional 90 minutes, 120/277 VAC, 60Hz, Emergency Backup.
- ENERGY STAR® Certified.
- Flicker-Free Dimming. Special order Lutron Hi-lume-Series Drivers.
- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Cedar™ System 4" LED Light Engines.

Technical Details

Construction:

- Single wall IC rated for direct contact with insulation. For use in IC and non-IC conditions. 850 lumens.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.

Installation:

- Designed for ceiling plenums where 2x6 joists or taller are used.
- High strength hanger bars can easily be nailed to joists.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Hanger Bars: Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

Electrical:



- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.95.

Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 1% with compatible dimmer.
- Can be specified with Lutron drivers for specific applications.
- For full list of dimmers refer to the Dimmer Compatibility List.

Listings: UL Listed for Damp Location and for Wet Location with select trims. UL Listed for Direct Contact with Insulation and Combustible Material. UL Listed for Feed Through.

Dimensions



Product Numbers

Item	Lumens	Voltage	Dimming
E4LC08ICA	850 lm	120V	Triac/ELV
E4LC08ICAD	850 lm	120/277V	Triac/ELV/0-10V
E4LC08ICASD	850 lm	120/277V	Sunset
E4LC08ICAL	850 lm	120/277V	Lutron EcoSystem

Product Number Builder Example: E4LC08ICA

ELCO Cedar 4" Housing

Lumens

IC Airtight

Dimming

Optional

E4LC

08 850 lm

ICA ICA

(Blank) 120V Triac/ELV
D 120/277V Triac/ELV/0-10V
SD Sunset
L Lutron

No EM
EM1 Emer. Backup up to 700 lm
EM2 Emer. Backup to 1100 lm