

Project name:

Fixture type:

Date:

# 6" Canless Koto™ IC New Construction Frame

IC Rated for direct contact with insulation. Easy-to-remove driver included on frame. To be used with Canless Koto™ LED Modules.

#### Features

- Must be used with Canless Koto<sup>™</sup> LED Modules
- IC Rated for direct contact with insulation
- Easy-to-removed driver included
- Driver specified for 120V (Triac/ELV) or 120/277V (0-10V/Triac/ELV)

### **Technical Details**

Construction: IC rated for direct contact with insulation. For use in IC and Non-IC conditions.

**Installation:** High strength hanger bars can easily be nailed to joists. Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.


**Hanger Bars:** Pre-Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

**Electrical:** Driver is rated for 120V or 120/277V input. High Efficiency driver with a power factor > 0.95.

**Dimmability:** Option ELV/TRIAC dimming or 3 in 1 dimming: Triac, ELV and 0-10V dimming can be specified.



#### Dimensions



#### **Product Numbers**

Item	Description	Lumens	Watts	Voltage	Dimming
E6KCL10IC		950 lm	11.9W	120V	Triac/ELV
E6KCL10IC-EM1	90 min. Emergency Battery Backup	950 lm	11.9W	120V	Triac/ELV
E6KCL10ICDX		950 lm	11.9W	120/277V	0-10V/Triac/ELV
E6KCL10ICDX-EM1	90 min. Emergency Battery Backup	950 lm	11.9W	120/277V	0-10V/Triac/ELV

## Product Number Builder Example: E6KCL10IC

6" Canless Koto™ IC New Construction Frame

Dimming - Voltage

E6KCL10IC

Triac/ELV - 120V **DX** 0-10V/Triac/ELV -120/277V

Specifications

11.9W

950 lm

Triac/ELV, 0-10V/Triac/ELV

120/277V or 120V

Wattage

Lumens

Voltage

Dimmable

Optional

Standard

-EM1 EM Battery Backup