

Project name:

Fixture type:

Date:

# **4" Sunset Dimming LED Reflector Insert - EL415SD**

ELCO Lighting's inserts are engineered with energy-efficient LED technology that produces even illumination with an incredible 93+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life of 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings manufactured by ELCO or others. The best green choice for simple residential lighting projects.


#### Features

- Fits ELCO 4" Dedicated LED Recessed Housings, Regular and Shallow.
- · Soft white lens provides smooth lumen distribution and eliminates LED pixelation.
- · Deep set LED trim reduces glare while providing area illumination.
- · CA Title 24, ENERGY STAR, JA8-2016-E.
- Life Span of 50,000 hours L70.

#### Specifications

Wattage	10W			
Lumens	600 lm			
Voltage	120V			
Color Temp.	3000 - 1800K			
Dimmable	Triac/ELV			
Lamp Type	LED			
Beam Angle	90°			
Wet Location	Listed			

#### Dimensions



### Product Numbers

ltem	Lamp type	Lumens	сст	Watts	Voltage	Dimming	Beam Angle	Finish
EL415SDW	LED	600 <b>i</b> m	3000 - 1800K	10W	120V	Triac/ELV	90°	White
EL415SDBZ	LED	600 <b>i</b> m	3000 - 1800K	10W	120V	Triac/ELV	90°	Bronze

#### **Technical Details**

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED Array technology.

Construction: For use in IC and non-IC housings. Spun Aluminum for greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

Installation: Includes PSA30 medium base adapter for retrofitting existing housings. Quick connect for use with ELCO housings EL490ICA, EL490RICA, EL492ICA, EL492RICA, EL49FICA. PSA30 (Medium Base Socket adapter) allows for use with EL99ICA, EL99RICA, EL99FICA, EL99A, EL99RA. PSA31 (GU10 Socket Adapter, not included) allows for use with EL49ICA, EL49A, EL49RA. PSA35 (GU24 Socket Adapter, not included) allows for use with EL99ICA-G24, EL99RICA-G24. Can be used in IC and non-IC housings.

Electrical: Driver connects to 120V power supply. High Efficiency driver with a power factor > 0.9. Start time of less than .75 seconds.

LED Technology: Extremely accurate color rendering with 93+ CRI. Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integral heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Works with 120V Triac and ELV type dimmers . Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List.

Listings: UL Listed for Wet Location. RoHS Compliant. ENERGY STAR® Certified. California Title 24 JA8-2016-Ε.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

## Product Number Builder

Example: EL415SDW

4" LED Reflector Insert Finish EL415SD W White

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com © ELCO Lighting 2018. All rights reserved • Rev. 09 Jan 2018 • ELCO Lighting reserves the right to make specification and design changes without notice. BZ Bronze