

# 6" LED IC Airtight Sloped Ceiling Remodel Housing - EL970RICA



ELCO Slant allows for installation in sloped ceilings ranging from 2/12 (10°) to 12/12 (45°). Can be used in insulated ceilings. Fits in 2" x 8" joist construction.


## Features

- 6" Sloped Remodel Single Wall Housing.
- IC Airtight for use in insulated ceilings.
- California Title 24 (JA8-2016-E).

## Specifications

<b>Wattage</b>	24W
<b>Voltage</b>	120V
<b>Damp Location</b>	UL listed

## Dimensions



## Technical Details

### Construction:

- IC Rated for Direct Contact with Insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Aluminum housing for greater heat dissipation.

**Installation:** Designed for ceiling plenums where 2x8 joists or taller are used. Template for hole cutout is provided with each housing. See installation sheet for detailed information.

**Junction Box:** Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and One 3/4" knockout. Four true pry-out knockout slots for easy Romex installation.

### Electrical:

- Connection is rated for 120V or 277V input.
- For 277V step down to 120V housing consult factory.

**Trims:** Compatible with EL713, EL714, EL715, EL716 Series LED Inserts.

### Listings:

- UL Listed for Damp Location.
- UL Listed for Direct Contact with Insulation and Combustible Material.
- UL Listed for Feed Through.
- AirTight: Per ASTM E-283.C
- California Title 24 (JA8-2016-E).

**Warranty:** ELCO Products are built to last. 5-year Limited warranty.

## Product Numbers

Item	Watts	Voltage
EL970RICA	24W	120V