

24V DC Koto™ LED Module

Works with 2", 3" & 4" Koto™ 24V DC Recessed Housings and Koto™ Trims




Features

- 10W, 800 lm, 2700K, 24V DC input
- Integrated 24V DC Dimmable Driver for low voltage and PoE applications
- Standard 38° Lens installed, 25° and 60° lens included with each module - Optional Lens: 18° (EP731C)
- Optional: Louver (L45), Linear Lens (L46), Spread Lens (L47), Clear Lens (L48), Frosted Lens (L49), Snoot (L50), Color Shifter (L51)
- Works in 2", 3", 4", 5" & 6" ELCO Koto DC housings with Koto™ twist-&-lock trims
- Excellent color rendering 90+ CRI
- Title 24 JA8-2022 Compliant
- Meets Energy Star Requirements
- Covered by U.S. PATENTS and Patents Pending

Specifications

| | |
|--------------------|---------------|
| Wattage | 10W |
| Lumens | 800 lm |
| Voltage | 24V DC |
| Color Temp. | 2700K - 3000K |
| Lamp Type | LED |
| Beam Angle | 25°, 38°, 60° |
| CRI | 90 |

Dimensions



Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated 24V DC driver. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-lock design for toolless trim installation.

Electrical: Module connects to 24V DC power supply. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds. PoE ready.

LED Technology: Extremely accurate Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Dimmability: Dimming based on power supply.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Product Numbers

| Item | Lamp type | Lumens | CCT | Watts | Voltage | Beam Angle |
|-------------------|-----------|--------|-------|-------|---------|---------------|
| ELK0827-24 | LED | 800 lm | 2700K | 10W | 24V DC | 25°, 38°, 60° |
| ELK0830-24 | LED | 800 lm | 3000K | 10W | 24V DC | 25°, 38°, 60° |

Product Number Builder

Example: **ELK0827-24**

24V DC Koto™ LED Module

Lumens

Color Temp.

Voltage

ELK

08 800


27 2700K
30 3000K

-24 24V DC

Compatible Products

For use with 24V DC Koto™ LED Module

2" Koto™ Dedicated LED ICA Housings (24V DC Input)



24V DC 2" ICA Maximum Adjustability Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|-----------------------|
| E24V276ICA | Maximum Adjustability |

2" Pex™ Twist-On Trims



Round Deep Reflector

ELK2818
Finishes:
(W, B, H, BB, BZ)




Round Adjustable Reflector

ELK2829
Finishes:
(W, B, H, BB, BZ)




Round Adjustable Pinhole

ELK2827
Finishes:
(W, B, BB, BZ)



Square Deep Reflector

ELK2518
Finishes:
(W, B, BB)



Square Adjustable Reflector

ELK2529
Finishes:
(W, B, BB)



Square Reflector

ELK2541
Finishes:
(W, B, BB)




Square Adjustable Pinhole

ELK2527
Finishes:
(W, B, BB)



Round Gimbal

ELK2888
Finishes:
(W, B, BZ)



Square Gimbal

ELK2588
Finishes:
(W, BZ)

Compatible Products




For use with 24V DC Koto™ LED Module

3" Koto™ Dedicated LED ICA Housings (24V DC Input)




24V DC 2-Hour Fire Rated 3" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|-----------------------------|
| E24V39FICA | 7 1/2" Height - Sound Rated |



24V DC 3" ICA Maximum Adjustability Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|-----------------------|
| E24V386ICA | Maximum Adjustability |



24V DC 3" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|----------------|
| E24V390ICA | |



24V DC 3" ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|------------|----------------|
| E24V390ICA | |

3" Pex™ Twist-On Trims



Round Deep Reflector

ELK3618
Finishes:
(W, BB, BZ, B, C, H)



Round Adjustable Gimbal

ELK3629
Finishes:
(W, BB, BZ, B, C, H)



Round Adjustable Pinhole

ELK3627
Finishes:
(B, BB, BZ)



Round Adjustable Baffle

ELK3693
Finishes:
(W)




Round Adj. Slot Aperture

ELK3620
Finishes:
(W)



Round Adj. Wall Wash

ELK3622
Finishes:
(W)



Square Deep Reflector

ELK3318
Finishes:
(W, BB, BZ, B, C, H)




Square Adjustable Gimbal

ELK3329
Finishes:
(W, BB, BZ, B, C, H)




Square Adjustable Pinhole

ELK3327
Finishes:
(B, BB, BZ)




Square Reflector

ELK3341
Finishes:
(W, B, BB, BZ)



Square Adj. Wall Wash

ELK3322
Finishes:
(W)



Square Adjustable Baffle

ELK3393
Finishes:
(W)

Compatible Products

For use with 24V DC Koto™ LED Module

3" Pex™ Trimless *• Only for use with E24V386ICA*



Spackle Frame

EL3SFR



Adjustable Trimless Reflector

ELK315


Finishes:
(W, B, H)

3" Flush Mount Trim Adaptors



Round Flush Mount

EL3FMR




Square Flush Mount

EL3FMS

Compatible Products


For use with 24V DC Koto™ LED Module

4" Koto™ Dedicated LED ICA Housings (24V DC Input)




24V DC 4" ICA Maximum Adjustability Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|-----------------------|
| E24V485ICA | Maximum Adjustability |



24V DC 4" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|----------------|
| E24V490ICA | |



24V DC 4" R-60 Spray Foam Insulation
New Construction Housing

| CAT NO. | SPECIFICATIONS |
|--------------|---|
| E24V490AJICA | Maximum Adjustability, For use in R60 or Chicago plenum applications |



24V DC 4" ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| E24V490RICA | |



24V DC 2-Hour Fire Rated 4" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|------------------------------|
| E24V48FICA | 7 1/2" Height Sound Rated |

4" Pex™ Round Twist-On Trims



Reflector
ELK4118
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Gimbal
ELK4129
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Pinhole
ELK4127
Finishes:
(B, BB, BZ)



Adjustable Baffle
ELK4193
Finishes:
(W, BB, B)



Slot Aperture
ELK4130
Finishes:
(W)



Rotatable Slot Aperture
ELK4120
Finishes:
(W)



Adj. Wall Wash
ELK4122
Finishes:
(W)

Compatible Products

For use with 24V DC Koto™ LED Module

4" Pex™ Square Twist-On Trims



Reflector
ELK4218
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Gimbal
ELK4229
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Pinhole
ELK4227
Finishes:
(B, BB, BZ)




Adjustable Phenolic Baffle
ELK4293
Finishes:
(W, BB, B)




Adj. Slot Rotatable Aperture
ELK4220
Finishes:
(W)



Adjustable Wall Wash
ELK4222
Finishes:
(W)



Adjustable Reflector
ELK4282
Finishes:
(W)



Adjustable Baffle
ELK4284
Finishes:
(W)


4" Flexa™ Twist-On Trims




Round Reflector
ELK4721
Finishes:
(WW, BB, BZBZ, BW, CC, CW, HW, CN)




Round Baffle
ELK4723
Finishes:
(WW, BB, BZBZ, BW)



Square Reflector
ELK4741
Finishes:
(WW, BB, BZBZ, BW, HW)
**Not for Remodel Housing*



Square Baffle
ELK4743
Finishes:
(WW, BB, BZBZ, BW)
**Not for Remodel Housing*



Adjustable Square Reflector
ELK4759
Finishes:
(WW, BB, B, H)

Compatible Products

For use with 24V DC Koto™ LED Module

4" Pex™ Trimless • *Only for use with E24V485ICA & E24V490AJICA*



**Round Spackle
Frame Only**
EL4SFR



Round Smooth Reflector
ELK408
Finishes:
(W, B, BZ, H)



**Round Adjustable
Reflector**
ELK415
Finishes:
(W, B, BZ, H)




**Adjustable Reflector
with Spackle Frame**
ELK430
Finishes:
(W, B, BZ, H)



**Adjustable Baffle
with Spackle Frame**
ELK434
Finishes:
(W, B, BZ)



Sq. Spackle Frame
EL4SFS



Sq. Smooth Reflector
ELK445
Finishes:
(W, B, H)



Sq. Adjustable Reflector
ELK459
Finishes:
(W, B, H)

4" Flush Mount Trim Adaptors



Round Flush Mount
EL4FMR
*For use with
ELK41 & Unique™ Trims*



Square Flush Mount
EL4FMS
*For use with
ELK42 Trims*

Compatible Products




For use with 24V DC Koto™ LED Module

6" Koto™ Dedicated LED ICA Housings (24V DC Input)



24V DC 2-Hour Fire Rated 6" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|----------------|
| E24V76FICA | 7 ¾" Height |




24V DC 6" Standard ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------------|--------------------------|
| E24V770ICA | 7 ½" Height |
| E24V770ICA-EM5 | Battery Backup, 24W MAX. |




24V DC 6" Standard ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| E24V770RICA | 7 ½" Height |



24V DC 2-Hour Shallow Fire Rated 6" ICA
New Construction Housing

| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| E24V75FICAS | 6 ¾" Height |



24V DC 6" Shallow ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------------|--------------------------|
| E24V760ICA | 5 ½" Height |
| E24V760ICA-EM5 | Battery Backup, 24W MAX. |



24V DC 6" Shallow ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| E24V760RICA | 5 ½" Height |

6" Twist-On Trims




Round Reflector

ELK610
Finishes:
(WW, BB, BZBZ, BW,
CC, CW, CN, HW)



Adjustable Round Reflector

ELK629
Finishes:
(WW, BB, BZBZ,
BW, CW, HW)



Adjustable Round Baffle

ELK693
Finishes:
(WW, BB, BZBZ, BW)



Round Deep Reflector

ELK6418
Finishes:
(W, BB, BZ, H)



Adjustable Slot Aperture

ELK6420
Finishes:
(W)

6" Unique™ Twist-On Trims



Round Reflector

ELK6710
Finishes:
(W, B, BZ)



Round Baffle

ELK6713
Finishes:
(W, BZ)



Round Wall Wash

ELK6715
Finishes:
(W, BZ)

Compatible Products

For use with 24V DC Koto™ LED Module

24V DC Transformers



**Electronic Low Voltage
Dimmable Driver**

| CAT NO. | SPECIFICATIONS |
|------------|-----------------|
| DRVE24V60W | 60W, 120V Input |



**Constant Voltage
LED Driver**

| CAT NO. | SPECIFICATIONS |
|---------|----------------------|
| DRV60W | 60W, 120/277V Input |
| DRV100W | 100W, 120/277V Input |



**0-10V
Dimmable Driver**

| CAT NO. | SPECIFICATIONS |
|-----------|---------------------|
| DRV30W-10 | 30W, 120/277V Input |
| DRV60W-10 | 60W, 120/277V Input |
| DRV96W-10 | 96W, 120/277V Input |




**Lutron™ Hi-Lume 1%
LED Driver**

| CAT NO. | SPECIFICATIONS |
|-----------|------------------------------------|
| DRVLT40W | 40W, Triac, 120/277V |
| DRVLT340W | 40W, Lutron Ecosystem, 120/277V |



**Lutron™ Hi-Lume Premiere 0.1%
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|----------|--|
| DRVL396W | 96W, Lutron Ecosystem, 120/277V Input |



**Universal (Small)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|-------------|--------------------------------------|
| DRVU24V24WD | 24W, 24V DC (1A), Triac/ELV/MLV |
| DRVU24V60WD | 60W, 24V DC (2.5A), Triac/ELV/MLV |



**Universal (Medium)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|--------------|-------------------------------------|
| DRVU24V100WD | 100W, 24V DC (4A), Triac/ELV/MLV |




**Universal (Large)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|--------------|-------------------------------------|
| DRVU24V200WD | 200W, 24V DC (8A), Triac/ELV/MLV |



**Universal (X-Large)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|--------------|--------------------------------------|
| DRVU24V300WD | 300W, 24V DC (12A), Triac/ELV/MLV |



**Electronic (Large)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|-------------|---------------------------|
| DRVE24V48DW | 48W, 24V DC (2A), Triac |
| DRVE24V60DW | 60W, 24V DC (2.5A), Triac |
| DRVE24V96DW | 96W, 24V DC (4A), Triac |



**Dimmer
with Built-in Driver**


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| DIMTP2 | 60W, 120V |
| DIMTP3 | 100W, 120V |

Photometric Report

24V DC Koto™ LED Module

PHOTOMETRIC REPORT

Product #: ELK0827-24 (36°)
 Wattage / Lumens: 10W / 860.2 lm
 Luminaire LPW: 86 lm/W



CANDLE POWER SUMMARY

| Degree Vertical | 0° |
|-----------------|------|
| 0 | 2329 |
| 5 | 2082 |
| 15 | 1212 |
| 25 | 301 |
| 35 | 61 |
| 45 | 35 |
| 55 | 22 |
| 65 | 12 |
| 75 | 5 |
| 85 | 0 |
| 90 | 0 |

ILLUMINANCE AT A DISTANCE


| Distance to Target Plane | Center Beam Footcandles | Beam Diameter |
|--------------------------|-------------------------|---------------|
| 4' | 146 | 2.4' |
| 6' | 64.7 | 3.5' |
| 8' | 36.4 | 4.7' |
| 10' | 23.3 | 5.9' |

ZONAL LUMEN SUMMARY

| Zone | Lumens | %Luminaire |
|-------|--------|------------|
| 0-30° | 754.8 | 87.3 |
| 0-40° | 806.2 | 93.2 |
| 0-60° | 850.3 | 98.3 |
| 0-90° | 864.6 | 100 |

PHOTOMETRIC REPORT

Product #: ELK0830-24 (36°)
 Wattage / Lumens: 10W / 901.2 lm
 Luminaire LPW: 90.1 lm/W



CANDLE POWER SUMMARY

| Degree Vertical | 0° |
|-----------------|------|
| 0 | 2426 |
| 5 | 2169 |
| 15 | 1262 |
| 25 | 314 |
| 35 | 64 |
| 45 | 37 |
| 55 | 23 |
| 65 | 12 |
| 75 | 6 |
| 85 | 0 |
| 90 | 0 |

ILLUMINANCE AT A DISTANCE

| Distance to Target Plane | Center Beam Footcandles | Beam Diameter |
|--------------------------|-------------------------|---------------|
| 4' | 152 | 2.4' |
| 6' | 67.4 | 3.5' |
| 8' | 37.9 | 4.7' |
| 10' | 24.3 | 5.9' |

ZONAL LUMEN SUMMARY

| Zone | Lumens | %Luminaire |
|-------|--------|------------|
| 0-30° | 786.2 | 87.3 |
| 0-40° | 839.8 | 93.2 |
| 0-60° | 885.7 | 98.3 |
| 0-90° | 900.6 | 100 |