

4" 0-10V LED Inserts with 5-CCT and 3-Lumen Switch

This unique Ply System 0-10V dimmable LED Insert gives you the options you are looking for in one fixture. Engineered with energy-efficient LED technology and with a 120/277V 0-10V dimmable driver for a budget friendly 0-10V solution. Switch to desired Color Temperature (2700K, 3000K, 3500K, 4000K or 5000K) and Lumen Output (850 lm, 1000 lm, 1500 lm) by using manual switch located on module. Designed to be used for New Construction, Remodel with ELCO Ply™ System Housings or as a retrofit with existing housings.



Features

- Manual switch to choose desired Color Temperature and Lumen Output
- 0-10V Dimmable
- 120/277V Driver
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation
- Deep set LED trim reduces glare while providing even illumination
- 90+ CRI for extremely accurate color rendering
- CA Title 24, ETL listed, ENERGY STAR, JA8-2016-E
- Life span of 50,000 hours L70
- Patent Pending

Specifications

Wattage	9.5, 13.5, 18W
Lumens	850, 1000, 1500 lm
Voltage	120/277V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	0-10V
Lamp Type	LED
CRI	90+
Wet Location	Listed

Options



All White

All Black

All Haze



Haze/White Trim

Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly while reducing glare with LED technology.

Construction: For use in IC and non-IC applications. High quality powder coat prevents rust and cracking.

Installation: For use with ELCO 4" Ply™ Housings EL49FICDXA, EL49FICDXA-B, EL490ICDXA, EL490ICDXA-B, EL490ICDXA-EM5, EL490ICDXA.

Electrical: 120/277V Input. Power factor > 0.9 Start time of less than .75 seconds.


LED Technology: Extremely accurate color rendering with 93+ CRI. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Works with 0-10V dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List. Dims with no hot spots or flickering.

Listings: UL Listed for Wet Location. RoHS Compliant. ENERGY STAR® Certified. California Title 24 JA8-2016-E.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Dimensions



Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
EL475CT5DW	LED	850	2700K,	9.5	120/277V	0-10V	All White
		1000	3000K,	13.5			
		1500 lm	3500K, 4000K, 5000K	18W			
EL475CT5DH	LED	850	2700K,	9.5	120/277V	0-10V	All Haze
		1000	3000K,	13.5			
		1500 lm	3500K, 4000K, 5000K	18W			

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
EL475CT5DBB	LED	850, 1000, 1500 lm	2700K,	9.5, 13.5, 18W	120/277V	0-10V	All Black
			3000K,				
			3500K,				
			4000K, 5000K				
EL475CT5DHW	LED	850, 1000, 1500 lm	2700K,	9.5, 13.5, 18W	120/277V	0-10V	Haze with White Trim
			3000K,				
			3500K,				
			4000K, 5000K				

Product Number Builder Example: EL475CT5DW

ELCO 4" LED Inserts

Color Temp.

Finish

EL475

CT5 2700K-5000K

DW All White

DBB All Black


DH All Haze

DHW Haze with White Trim

Compatible Products

For use with 4" 0-10V LED Inserts with 5-CCT and 3-Lumen Switch


4" 0-10V Dedicated LED Housings



4" 0-10V Dedicated LED Housing
New Construction



4" 0-10V Dedicated LED Housing
Remodel



2-Hour Fire Rated
4" 0-10V Dedicated LED Housing
New Construction

CAT NO.	SPECIFICATIONS
EL490ICDXA	14W, 120/277V
EL490ICDXA-B	Butterfly Bracket
EL490ICDXA-EM5	Emergency Back-Up

CAT NO.	SPECIFICATIONS
EL490RICDXA	14W, 120/277V


CAT NO.	SPECIFICATIONS
EL49FICDXA	7 3/4" Height - 14W, 120/277V
EL49FICDXA-B	Butterfly Bracket

4" Accessories



Hanger Bars
for Butterfly Bracket

CAT NO.	SPECIFICATIONS
FB27	Set of two 27" flat hanger bars for wood construction



Hanger Bars
for Butterfly Bracket

CAT NO.	SPECIFICATIONS
CH26	Set of two 26" C-Channel hanger bars for T-Bar ceiling



Emergency Battery Backup

CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V



ELCO Lighting

Dimmer Compatibility Chart

0-10V Dimming LED Inserts

EL495&695

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
120/277 V			
Lutron	Diva® 0-10V Single Pole/3-Way Dimmer	DVSTV-WH	10% - 100%
	Nova T® 0-10V Single Pole Slide-to-Off Dimmer	NTSTV-DV-WH	10% - 100%
Philips	Sunrise 0-10V 3-Way LED, Fluorescent Preset Slider Dimmer	SR1200ZTUNV	10% - 100%

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.