

Pex™ 3" Round Adjustable Slot Aperture

Pex™ Precision die-cast adjustable trims with twist-&-lock system for easy Koto™ Module installation



Features

- 45° Adjustability.
- 4 3/8" O.D.
- Convenient twist-lock design for easy installation.
- Lamp: Koto™ LED Module.
- Recommended to be used with Maximum Adjustability Housings

Technical Details

- Construction:** Diecast aluminum with a powder coated finish.
- Installation:** Twist-lock design allows for easy mounting onto the Koto™ LED Module.
- Compatible Housing:** Compatible with 3" housings.

With ELK07 & ELK09 Module:



- EL386ICA, EL390ICA, EL390ICA-EM5, EL390RICA & EL39FICA

With ELK19 & ELK21 Module:

- E3LK76ICA, E3LK77ICAD, E3LK65ICA, E3LK65ICA-EM1, E3LK66ICAD, E3LK66ICAD-EM1, E3LK65RICA, E3LK39FICA & E3LK39FICAD

Lamp: Koto™ LED Module only.

Dimensions



Product Numbers

Item	Finish
ELK3620W	Black Slot/White Ring

Product Number Builder Example: ELK3620W

Pex™ 3" Adjustable Slot Aperture

Finish

ELK3620

W Black Slot/White Ring

Compatible Products

For use with Koto™ System 3" Trims



Koto™ LED Module



ELK07, ELK09
Koto™ LED Module

PRODUCT NUMBER BUILDER			
Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
	07 750 lm	27 2700K	(blank) 38° lens (Standard)
	09 950 lm	30 3000K	-S 18° lens
		35 3500K	-N 25° lens
		40 4000K	-W 60° lens
		SD Sunset Dimming	

ACCESSORIES



Lens
EP731C 18° Lens
EP732C 25° Lens
EP734C 60° Lens



Reflectors
EP735C 15°
EP736C 25°
EP737C 38°
EP738C 60°



Hex Louver
L45
For a better glare shield



Linear Louver
L46
For a wide rectangular illumination pattern




Spread Louver
L47
For a symmetrical broadening of light beams

3" Koto™ Dedicated LED ICA Housings



2-Hour Fire Rated
3" ICA Housing - 7 3/4" Height
New Construction

CAT NO.	SPECIFICATIONS
EL39FICA	Sound Rated



3" ICA Maximum Adjustability
Housing - 5 1/2" Height
New Construction

CAT NO.	SPECIFICATIONS
EL386ICA	Maximum Adjustability



3" ICA Housing - 5 1/2" Height
New Construction

CAT NO.	SPECIFICATIONS
EL390ICA	
EL390ICA-EM5	Emergency Battery Back-up (90 minutes)



3" ICA Housing - 5 1/2" Height
Remodel

CAT NO.	SPECIFICATIONS
EL390RICA	

Compatible Products

For use with Koto™ System 3" Trims



Koto™ Architectural LED Light Engine



ELK19 ELK21
Koto™ LED Light Engine

PRODUCT NUMBER BUILDER			
Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
	19 850 lm	27D 2700K	(blank) 38° lens (Standard)
	21 1100 lm	30D 3000K	-S 18° lens
		35D 3500K	-N 25° lens
		40D 4000K	-W 60° lens
		SDD Sunset Dimming	

ACCESSORIES



Lens
EP731C 18° Lens
EP732C 25° Lens
EP734C 60° Lens



Reflectors
EP735C 15°
EP736C 25°
EP737C 38°
EP738C 60°



Hex Louver
L45
For a better glare shield



Linear Louver
L46
For a wide rectangular illumination pattern




Spread Louver
L47
For a symmetrical broadening of light beams

3" Architectural Koto™ LED ICA Recessed Housings



2-Hour Fire Rated
4" ICA Housing - 7 1/2" Height
New Construction

CAT NO.	SPECIFICATIONS
ELK72FICA	120V - Triac/ELV
ELK73FICAD	120/277V - 0-10V/Triac/ELV



3" ICA Shallow Maximum Adjustability Housing
4" Height - Easy-to-Remove Driver
New Construction

CAT NO.	SPECIFICATIONS
E3LK76ICA	120V - Triac/ELV
E3LK77ICAD	120/277V - 0-10V/Triac/ELV




3" ICA Housing - 5 1/2" Height
New Construction

CAT NO.	SPECIFICATIONS
E3LK65ICA	120V - Triac/ELV
E3LK65ICA-EM1	120V - Triac/ELV Emergency Battery Back-up (90 min)
E3LK66ICAD	120/277V 0-10V/Triac/ELV
E3LK66ICAD-EM1	120/277V 0-10V/Triac/ELV Emergency Battery Back-up (90 minute)



4" ICA Housing - 5 1/2" Height
Remodel

CAT NO.	SPECIFICATIONS
E3LK65RICA	120V - Triac/ELV



3" ICA High Lumen Housing (1500 lm)
5 1/2" Height - Easy-to-Remove Driver
New Construction

CAT NO.	SPECIFICATIONS
E3LK85ICAD	120/277V - 0-10V/Triac/ELV