

Pex™ 4" Round Adjustable Wall Wash

Pex™ Precision die-cast adjustable trims with twist-&-lock system for easy Koto™ Module installation



Features

- 4" Round Adjustable Reflector Wall Wash
- 45° Adjustability
- 5" O.D.
- Convenient twist-lock design for easy installation
- Lamp: Koto™ LED Module
- Recommended to be used with Maximum Adjustability Housings

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module.

Compatible Housing: Compatible with 4" housings.

With ELK07 & ELK09 Module:



- EL485ICA, EL490ICA, ELK490ICA-EM5, EL490RICA & EL49FICA

With ELK19 & ELK21 Module:

- E4LK98ICA, E4LK99ICAD, E4LK87ICA, E4LK87ICA-EM1, E4LK88ICAD, E4LK88ICAD-EM1, E4LK87RICA, E4LK88RICAD, ELK49FICA & ELK49FICAD

Lamp: Koto™ LED Module.

Dimensions



Product Numbers

Item	Finish
ELK4122W	All White

Product Number Builder Example: ELK4122W

Pex™ 4" Round Adjustable Reflector Wall Wash	Finish
ELK4122	W All White

Compatible Products



For use with Koto™ System 4" Trims

Koto™ LED Module



ELK07, ELK09
Koto™ LED Module

PRODUCT NUMBER BUILDER

Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
	07 750 lm	27 2700K	(blank) 38° lens (Standard)
	09 950 lm	30 3000K	-S 18° lens
		35 3500K	-N 25° lens
		40 4000K	-W 60° lens
		SD Sunset Dimming	

ACCESSORIES



Lens

EP731C 18° Lens
EP732C 25° Lens
EP734C 60° Lens



Reflectors

EP735C 15°
EP736C 25°
EP737C 38°
EP738C 60°



Hex Louver L45

For a better glare shield



Linear Louver L46

For a wide rectangular illumination pattern



Spread Louver L47

For a symmetrical broadening of light beams



Clear Lens L48

Protective clear glass lens

4" Koto™ Dedicated LED ICA Housings



2-Hour Fire Rated
4" ICA Housing - 7 ½" Height
New Construction

CAT NO.	SPECIFICATIONS
EL49FICA	



4" ICA Maximum Adjustability
Housing - 5 ½" Height
New Construction

CAT NO.	SPECIFICATIONS
EL485ICA	Maximum Adjustability



4" ICA Housing - 5 ½" Height
New Construction

CAT NO.	SPECIFICATIONS
EL490ICA	
EL490ICA-EM5	Emergency Battery Back-up (90 minutes)



4" ICA Housing - 5 ½" Height
Remodel

CAT NO.	SPECIFICATIONS
EL490RICA	

Compatible Products

For use with Koto™ System 4" Trims



Koto™ Commercial Construction LED Light Engine



ELK19 ELK21
Koto™ LED Light Engine

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
	19 850 lm	27D 2700K	(blank) 38° lens (Standard)
	21 1100 lm	30D 3000K	-S 18° lens
		35D 3500K	-N 25° lens
		40D 4000K	-W 60° lens
		SDD Sunset Dimming	

ACCESSORIES



Lens
EP731C 18° Lens
EP732C 25° Lens
EP734C 60° Lens



Reflectors
EP735C 15°
EP736C 25°
EP737C 38°
EP738C 60°



Hex Louver
L45
For a better glare shield



Linear Louver
L46
For a wide rectangular illumination pattern



Spread Louver
L47
For a symmetrical broadening of light beams



Clear Lens
L48
Protective clear glass lens

4" Commercial Construction Koto™ Dedicated LED ICA Housings



2-Hour Fire Rated
4" ICA Housing - 7 1/2" Height
New Construction



4" ICA Shallow Maximum
Adjustability Housing - 4" Height
New Construction



4" ICA Housing - 5 1/2" Height
New Construction

CAT NO.	SPECIFICATIONS
ELK49FICA	120V - Triac/ELV
ELK49FICAD	120/277V - 0-10V/Triac/ELV

CAT NO.	SPECIFICATIONS
E4LK98ICA	120V - Triac/ELV
E4LK99ICAD	120/277V - 0-10V/Triac/ELV

CAT NO.	SPECIFICATIONS
E4LK87ICA	120V - Triac/ELV
E4LK87ICA-EM1	120V - Triac/ELV Emergency Battery Back-up (90 min)
E4LK88ICAD	120/277V - 0-10V/ Triac/ELV
E4LK88ICAD-EM1	120/277V - 0-10V/ Triac/ELV Emergency Battery Back-up (90 minute)



4" ICA Housing - 5 1/2" Height
Remodel

CAT NO.	SPECIFICATIONS
E4LK87RICA	120V - Triac/ELV
E4LK88RICAD	120/277V - 0-10V/Triac/ELV