


# 4" Remodel IC Airtight Housing 0-10V, 120/277V for 2-Hr Fire Rated Ceilings



Maximum 2-Hour Fire Rated ceiling assembly can be maintained when installed according to the International Building Code, Section 714.


## Features

- Remodel IC Airtight Housing **for 2-Hour Fire Rated ceilings**
- Round opening for easy hole cutting
- For use with EL495 Series Only
- Maximum 2-Hour Fire Rated ceiling assembly can be maintained when installed according to the International Building Code, Section 714
- Covered by U.S. Patents
- **NOTE:** Remodel tabs will not be completely covered by trims, painting may be required after installation or use of Oversized Ring (ELJ40V) to cover tabs
- JA8 2022 E-Compliant
- ETL Listed

## Specifications

|          |          |
|----------|----------|
| Voltage  | 120/277V |
| Dimmable | 0-10V    |

## Dimensions



## Technical Details

**Installation:** Remodel tabs for easy installation. See installation sheet for detailed information

**Mounting:** Pre-installed remodel clips for easy installation.

**Dimmability:** Dimmability based on lamp.

**Listings:** IC Rated for direct contact with insulation. For 2-Hr Fire Rated ceilings. cUL listed under UL 514A Standards as a metallic outlet box

**Compatible With:** 4" 0-10V DX Koto™ Fixtures, 0-10V LED Sky™ Panels, and 4" 0-10V LED Inserts (EL495 Series)

## Product Numbers


| Item          | Description              | Voltage  | Dimming |
|---------------|--------------------------|----------|---------|
| EJB4RICDXA    | 4" O.D. x 4 1/2" H       | 120/277V | 0-10V   |
| EJB4RICDXA-EM | Emergency Battery Backup | 120/277V | 0-10V   |

# Compatible Products



For use with 0-10V, 120/277V Housings for 2-Hour Fire Rated Ceilings

## 0-10V DX Koto™ LED Module



0-10V DX Koto™  
LED Module  
ELK10DX

| PRODUCT NUMBER BUILDER |            |             |                            |                             |
|------------------------|------------|-------------|----------------------------|-----------------------------|
| Koto™ LED Module       | Lumens     | Voltage     | Color Temperature          | Beam Angle                  |
| ELK                    | 10 1000 lm | DX 120/277V | 27 2700K                   | (blank) 38° lens (Standard) |
|                        |            |             | 30 3000K                   | -S 18° lens                 |
|                        |            |             | 35 3500K                   | -N 25° lens                 |
|                        |            |             | 40 4000K                   | -W 60° lens                 |
|                        |            |             | SD Sunset (3000K to 1800K) |                             |

### ACCESSORIES



#### Lens

EP731C 18° Lens  
EP732C 25° Lens  
EP733C 38° Lens  
EP734C 60° Lens

\*EP732C, EP733C, EP734C Included



#### Shoot

L50W White  
L50B Black



#### Secondary Optics

L45 Hex Louver (Black)  
L57 Hex Louver (White)  
L46 Linear Lens  
L47 Spread Louver  
L49 Frosted Lens  
L51 Color Shifter  
L52 Blue Optic Lens  
L53 Pink Optic Lens

## 4" Pex™ Twist-On Trims



Adjustable Gimbal

ELK4129

Finishes:

(W, BB, BZ, B, C, H)



Adjustable Pinhole

ELK4127

Finishes:

(W, BB, BZ, B, H, CP)




Shallow Reflector

ELK4116

Finishes:

(W, H)




Adjustable Gimbal

ELK4229

Finishes:

(W, BB, BZ, B, C, H)




Adjustable Pinhole

ELK4227

Finishes:

(W, BB, BZ, B, N)



Shallow Reflector

ELK4216

Finishes:

(W, H)

## 4" Unique™ Twist-On Trims




Shallow Reflector

ELK4710

Finishes:

(W, B, BZ)



Shallow Baffle

ELK4713

Finishes:

(W, BZ)



Wall Wash

ELK4715

Finishes:

(W, BZ)




Adjustable Spot

ELK4188

Finishes:

(W, B, BZ)




Square Reflector

ELK4714

Finishes:

(W, B, BZ)



Square Baffle

ELK4716

Finishes:

(W, BZ)


## 4" Flush Mount Trim Adaptors



### Round Adaptor

EL4FMR

• Compatible with ELK4116, ELK4127, ELK4129, ELK4710, ELK4713, ELK4715



### Square Adaptor

EL4FMS

• Compatible with ELK4216, ELK4227, ELK4229,

\*Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring

# Compatible Products

For use with 0-10V, 120/277V Housings for 2-Hour Fire Rated Ceilings



## 4" 120/277V, 0-10V LED Inserts



### Round Insert

**EL495**

Finishes:

(DW, DHW, DCW)

#### PRODUCT NUMBER BUILDER

| 4" 120/277V LED Inserts | Color Temperature        | Finish                         |
|-------------------------|--------------------------|--------------------------------|
| <b>EL495</b>            |                          |                                |
|                         | <b>30</b> 3000K (800 lm) | <b>DW</b> All White            |
|                         | <b>35</b> 3500K (850 lm) | <b>DHW</b> Haze w/White Ring   |
|                         | <b>40</b> 4000K (900 lm) | <b>DCW</b> Chrome w/White Ring |

## 120/277V, 0-10V Round LED Sky Panels™



### 0-10V Round LED Sky Panel™

| CAT NO.      | SPECIFICATIONS                         |
|--------------|----------------------------------------|
| ELSP63DXCT3W | White, 6", 14W, 1000 lm, 3000K - 4000K |
| ELSP63DXCT3B | Black, 6", 14W, 1000 lm, 3000K - 4000K |
| ELSP83DXCT3W | White, 8", 17W, 1400 lm, 3000K - 4000K |
| ELSP83DXCT3B | Black, 8", 17W, 1400 lm, 3000K - 4000K |