

FC-Line: Modern Trapezoid Wall Packs

3-CCT + 5-Power Selectable



Detail Specifications

- Finish: Bronze, Black, White, Custom finishes available
- IP Rating: Wet Location
- 3-CCT: 30/40/50k
- Impact Rating: IK08
- Beam Angle: Type III (Standard), II, IV available
- Chip: SMD 2835, R9 >50, CRI >80
- BUG: B3-U2-G2
- Operating Temperature: -40° - 122° F
- Lens: Clear acrylic with optics
- Average life (L70) of 70,000 hours

Applications:

- Walkways & Pathways
- Parking Lots
- Hospitality, Multi-Family
- Outdoor Corridors
- Residential, Commercial and Industrial

Product Information:

- Sturdy die-cast aluminum housing finished with corrosion free powder coat
- Full Cut-Off Dark Sky Compliant
- Photocell is included with an easy quick disconnect
- Instant-On to full brightness
- Select-n-Switch Technology: 3-CCT + 5-Power Selectable
- Control Options:
 - Standard Sensors
 - SILVAIR Bluetooth Mesh
 - ENVISIONLS Bluetooth
 - [Click Here](#) for More Information

Driver Options:

- UNV: 120-277V 0-10V Dimmable
- HV: 277-480V 0-10V Dimmable
- Built in 6Kv Surge Protector
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz

Certifications:

- UL Listed for USA and CA
- DLC Premium Listed
 - Pending ETA 04/2025
- ROHS Compliant
- Approved for CA T24
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

5P60		5P120	
WATT	LUMENS	WATT	LUMENS
20	2,900	80	11,600
30	4,350	90	13,050
40	5,800	100	14,500
50	7,250	110	15,950
60	8,700	120	17,400

Series	Finish ¹	Voltage	Photocell PC	Optic	Emergency	Surge Protector
LED-WPFC-TRZ-5P60-TRI 60/50/40/30/20w	BZ Bronze (Standard)	(blank) 120-277V	Photocell is included. Easy quick disconnect.	(blank) Type III	(blank) No Emergency	(blank) 6KV Built in
LED-WPFC-TRZ-5P120-TRI 120/110/100/90/80w	BL Black	HV 277-480V		T2 Type II	EMB 90 Minute Emergency Backup	20KV 20KV Surge Protector
	WH White			T4 Type IV	30-120F	
	GRY ¹ Gray					
	CS ¹ Custom Color					

¹. Standard quickship models shows on page 3.


Optional Accessories (Order Separately)	
Sensors	Sensor Remote
S-TWC-PIR-ON/OFF PIR Sensor On/Off Only 5/10/15min	S-LINE-R Remote for S-Line Sensor
S-TWC-PIR-1 PIR Bi-Level Motion + Daylight Sensor Remote Req'd)	ENVISION CONNECT Bluetooth smart app. Download on Apple or Android app store.
S-TWC-PIR-SL PIR SILVAIR Bluetooth Mesh	
S-TWC-PIR-BT PIR ENVISIONLS Bluetooth Control	

Specs and model numbers are subject to change with or without notice.


FEATURES



DIMENSIONS



5P60



5P120

STANDARD QUICK SHIP MODELS

Model	Voltage	Watts	Lumens	Color	CRI
LED-WPFC-TRZ-5P60-TRI-BZ-PC	120-277V	60/50/40/30/20W	8,700/7,250/5,800/4,350/2,900	30/40/50k	>80
LED-WPFC-TRZ-5P60-TRI-BL-PC	120-277V	60/50/40/30/20W	8,700/7,250/5,800/4,350/2,900	30/40/50k	>80
LED-WPFC-TRZ-5P60-TRI-WH-PC	120-277V	60/50/40/30/20W	8,700/7,250/5,800/4,350/2,900	30/40/50k	>80
LED-WPFC-TRZ-5P120-TRI-BZ-PC	120-277V	120/110/100/90/80W	17,400/15,950/14,500/13,050/11,600	30/40/50k	>80
LED-WPFC-TRZ-5P120-TRI-BL-PC	120-277V	120/110/100/90/80W	17,400/15,950/14,500/13,050/11,600	30/40/50k	>80
LED-WPFC-TRZ-5P120-TRI-WH-PC	120-277V	120/110/100/90/80W	17,400/15,950/14,500/13,050/11,600	30/40/50k	>80



S-TWC-PIR-ON/OFF



S-TWC-PIR-1
S-TWC-PIR-SL



S-LINE-R

SENSORS

Pre-Installed Accessory Model	Description
S-TWC-PIR-ON/OFF	PIR On/Off Only: Twist-C 5/10/15 Min
S-TWC-PIR-1	PIR Bi-Level + Daylight: Twist-C
S-TWC-PIR-SL	PIR SILVAIR Bluetooth Mesh
S-TWC-PIR-BT	PIR ENVISIONLS Bluetooth Control









REMOTE CONTROL

Accessory Model	Description
S-LINE-R	Remote for S-LINE Series Sensors

Specs and model numbers are subject to change with or without notice.

EnVisionLED™ Control Options

EnVision LED offers 3 control systems compatible with our LED Fixtures for projects of all sizes and budgets.

	Basic Controls	EnVisionLS 	EnVisionLED™ X SILVAIR 
Description	Standard Plug In Sensors	Basic Bluetooth Wireless Control	Advanced Bluetooth Wireless Control
Recommended Quantity (but not limited to)	N/A	>40-50 Nodes	>50 Nodes
Maximum Zone Quantity	N/A	100	3,000
Commissioning Tool	Remote Only	  ENVISIONLS App 	  SILVAIR App 
Commissioning Process	Individually Set via Remote	Wireless Must be done on site	Wireless- Initial linking must be done on site. Commissioning can be done via desktop remotely.
Floor Plan Upload	N/A	N/A	Yes Add a floor plan and mark luminaires & zones via desktop
Gateway	N/A	N/A	Required only for energy monitoring, advanced scheduling, automated demand response.
Individual Luminaire Control	Yes	Yes	Yes
Luminaire Grouping Zoning	N/A	Yes	Yes
High End Power Low End Power	Yes but limited (View Remote)	Yes	Yes
Cost	\$	\$\$	\$\$\$
DLC NLC Listed	N/A	Yes	Yes
Energy Monitoring & Data Reporting	N/A	N/A	Monitor energy usage per individual zone & retrofit cost savings calculation + detailed reporting







Compatible Products:

EnVision offers a variety of nodes, sensors, & gateways that are controlled via remote, ENVISIONLS Bluetooth Mesh & SILVAIR Bluetooth Mesh on all of our 0-10V dimmable fixtures.






Individual Fixture Controls: PIR Sensor, Bi-Level Dimming, Daylight


Basic Note: **-1** • ENVISIONLS Models Note: **-BT** • SILVAIR Models Note: **-SL**

	MODEL #	DESIGN	RECOMMENDED FIXTURE	FEATURES
	S-TWC-PIR-1 S-TWC-PIR-BT S-TWC-PIR-SL	Twist-C Control Sensor	Sensor Ready Fixtures: Area Lights, Canopies, Flood Lights, High Bays	All models are equipped with PIR occupancy sensing, high & low end bi-level dimming, & daylight sensing.
	S-TWC-90 + S-TWC-PIR-1 S-TWC-90 + S-TWC-PIR-BT S-TWC-90 + S-TWC-PIR-SL	Twist-C Control Sensor + 90 Degree Arm	Cylinders, Strips, Wall Packs	
	S-AUD-PIR-1 S-AUD-PIR-BT S-AUD-PIR-SL	2.5m Audio Jack	Panels & Troffers	
	S-SN-PIR-1 S-SN-PIR-BT S-SN-PIR-SL	Snap In Sensor	Troffers & Wraps	

Group Controls ENVISIONLS Models Note : **-BT** • SILVAIR Models Note: **-SL**

	MODEL #	DESIGN	VOLTAGE	FEATURES	RECOMMENDED FEATURES
	S-CM-PIR-LV-BT S-CM-PIR-LV-SL	Ceiling Mounted PIR Sensor	12-24V	PIR Sensor, Bi-Level Dimming, Daylight, 360° detection, 12' Max Mounting Height	Connects to 0-10V dimmable fixtures
	S-WM-PIR-CUNV-BT S-WM-PIR-CUNV-SL	Wall Mounted PIR Occupancy Sensor, Bi-Level Dimming, Daylight	120-277V	On/Off PIR occupancy sensor, 180° detection, 30' detection @ 4' Mounting Height	Connects to LED fixtures
	S-WS-120V-USB-SL		120V	Dimming Wall Socket, Two Sockets	Floor Lamps, Other Lamps

Gateway (Silvair Only) 4.5–5.5 V DC, 2A Power over Ethernet 36–57 V DC

	MODEL #	DESIGN	VOLTAGE	FEATURES	RECOMMENDED FEATURES
	SGW-102	Wall or Ceiling Mounted	POE	Advanced Energy Monitoring Control	Connects to Silvair Controls. Gateway is not required.