




Tubular T3 G4 Base



Key Features & Benefits

The new 12V T3 G4 base LED series integrates a set of SMD LED sources and is ideal to replace bi-pin G4 base **Incandescent** and **halogen** bulbs. Available: 1.5W, 2.5W, 3.5W options. This bulb is highly versatile, which can be used in landscape lighting, deck lighting to reading lights and offers significant energy savings and environmentally friendly. Light output is 360° which is perfect for even dispersion applications.

Technical Specifications:

Model Name	JQ-G4-A02K27[27K] JQ-G4-A02K30[30K]	JQ-G4-A03K27[27K] JQ-G4-A03K30[30K] JQ-G4-A04K30[45K]	JQ-G4-A04K27[27K] JQ-G4-A04K30[30K] JQ-G4-A04K30[45K]
Photo			
Halogen Replacement	20 Watt	30 Watt	35 Watt
Operating Voltage:	9 ~ 18V DC/AC	9 ~ 18V DC/ AC	9 ~ 18V DC/ AC
Power consumption:	1.5 Watt	2.5 Watt	3.5 Watt
Dimmable:*	YES	YES	YES
Dimensions:	0.94"x 0.39"D	1.06"x 0.47"D	1.26"x 0.55"D
CRI:	80	80	80
CCT Option:	2700K,3000K,4500K	2700K,3000K,4500K	2700k,3000K,4500K
Luminous Flux:	110 lm.	210 lm.	280 lm.
Operating Temperature:	-20° C - +50° C	-20° C - +50° C	-20° C - +50° C
Storage Temperature:	-30° C - +60° C	-30° C - +60° C	-30° C - +60° C
IP Rating	IP67	IP67	IP67
Rated Lifespan:	>25,000hrs.	>25,000hrs.	>25,000hrs.

Notes: Wattage +/- 10% ; Lumen Values +/- 5Lms. CRI +/- 5% ; Dimmable* fully tested with LUTRON© DILV magnetic low voltage dimmer or electrical dimmer with minimum load