


LUCIO – model: LED 6010

W Track System Luminaires



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Museum-quality LED luminaire with high performance optics.

FEATURES

- Recessed driver hidden in track
- Accommodates up to 1 lens and 1 glare control accessory
- 365° horizontal aiming and 90° indexed vertical aiming
- Integral selector to choose between independently controllable track circuits
- CBCP intensive ultra spot, 6010U
- Asymmetrical beam distribution, 6010A
- 50,000 rated life
- 5 year warranty

SPECIFICATIONS

- Construction:** Die-cast aluminum body with regressed driver.
- Input:** 120 VAC, 277VAC 50/60Hz
- Power:** 10W
- Light Source:** High output COB LED
- Dimming:** 100%-5% Electronic Low Voltage (ELV), TRIAC
- Standards:** UL & cUL Dry Location Listed, Title 24 JA8-2019 Compliant
- Finish:** Electrostatically powder coated White, Black, Platinum

Track	Model	Beam	Lumens @ 830	CBCP @ 830	Color Temp	CRI	Finish	
WTK WHK	120V 277V	6010	U 6°	620	37,915	827 2700K	85	BK Black PT Platinum WT White
			S 18°	910	4,845	830 3000K	85	
			N 25°	890	3,445	835 3500K	85	
			F 35°	910	2,230	840 4000K	85	
			A ASY	555	N/A	927 2700K	90	
						930 3000K	90	

WTK-6010 - ____ - ____

Example: WTK-6010N-930-WT

REPLACEMENT OPTICS

'U' and 'A' are dedicated optics

18°	REF-50BL10-S
25°	REF-50BL10-N
35°	REF-50BL10-F

Accommodates one lens accessory and one glare control accessory. 'U' and 'A' beam fixtures accept one glare control accessory.

LENS ACCESSORIES

Amber	LENS-16-AMB	Frosted Spread Beam Elongating	LENS-16-FR
Blue	LENS-16-BLU		LENS-16-SPR
Green	LENS-16-GRN		LENS-16-BEL
Red	LENS-16-RED		

GLARE CONTROL ACCESSORIES

Cross Louver	LENS-16P-CRL-BK	Snoot	LENS-16-SNOOT-BK
	LENS-16P-CRL-PT		LENS-16-SNOOT-PT
	LENS-16P-CRL-WT		LENS-16-SNOOT-WT
Honey Comb Louver	LENS-16-HCM		

wacighting.com Headquarters, East Manufacturing Facility South East Manufacturing Facility Central Manufacturing Facility West Manufacturing Facility
 Phone (800) 526.2588 44 Harbor Park Drive 1600 Distribution Ct 1700 South J Elmer Freeway, Ste 100 1750 S Archibald Ave
 Fax (800) 526.2585 Port Washington, NY 11050 Lithia Springs, GA 30122 Cedar Hill, TX 75104 Ontario, CA 91761

FIXTURE PERFORMANCE

Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6010U-827 WHK-6010U-827	6°	2700K	550	35,165	85
WTK-6010U-830 WHK-6010U-830		3000K	620	37,915	85
WTK-6010U-835 WHK-6010U-835		3500K	610	38,970	85
WTK-6010U-840 WHK-6010U-840		4000K	620	39,695	85
WTK-6010U-927 WHK-6010U-927		2700K	485	31,045	90
WTK-6010U-930 WHK-6010U-930		3000K	495	31,850	90

Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6010F-827 WHK-6010F-827	35°	2700K	800	1,850	85
WTK-6010F-830 WHK-6010F-830		3000K	910	2,230	85
WTK-6010F-835 WHK-6010F-835		3500K	870	2,010	85
WTK-6010F-840 WHK-6010F-840		4000K	925	2,130	85
WTK-6010F-927 WHK-6010F-927		2700K	680	1,565	90
WTK-6010F-930 WHK-6010F-930		3000K	700	1,640	90

Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6010S-827 WHK-6010S-827	18°	2700K	865	4,615	85
WTK-6010S-830 WHK-6010S-830		3000K	910	4,845	85
WTK-6010S-835 WHK-6010S-835		3500K	930	5,015	85
WTK-6010S-840 WHK-6010S-840		4000K	985	5,250	85
WTK-6010S-927 WHK-6010S-927		2700K	715	3,845	90
WTK-6010S-930 WHK-6010S-930		3000K	760	4,285	90

Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6010A-827 WHK-6010A-827	ASY	2700K	515	N/A	85
WTK-6010A-830 WHK-6010A-830		3000K	555		85
WTK-6010A-835 WHK-6010A-835		3500K	570		85
WTK-6010A-840 WHK-6010A-840		4000K	580		85
WTK-6010A-927 WHK-6010A-927		2700K	450		90
WTK-6010A-930 WHK-6010A-930		3000K	465		90

Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6010N-827 WHK-6010N-827	25°	2700K	845	3,285	85
WTK-6010N-830 WHK-6010N-830		3000K	890	3,445	85
WTK-6010N-835 WHK-6010N-835		3500K	900	3,525	85
WTK-6010N-840 WHK-6010N-840		4000K	960	3,760	85
WTK-6010N-927 WHK-6010N-927		2700K	700	2,720	90
WTK-6010N-930 WHK-6010N-930		3000K	735	2,945	90