

## NOX-432

### 4" Onyx Round Retrofit Baffle

Source: 10.5W or 14.5W LED  
650lm or 900lm

#### PRODUCT DESCRIPTION

Onyx Retrofit Series is suitable for use with most 4" recessed housings. Die-cast aluminum construction provides clean sharp edges. Deep regressed optics and round aperture delivers even and glare-free illumination. Available in multiple color temperatures and 90+ CRI.

#### FEATURES

- 650lm / 10.5W or 900lm / 14.5W
- 3500K, 4000K or 5000K @ 90+ CRI
- Integral dimmable driver
- Includes medium base socket adapter for easy retrofitting in 4" recessed housings
- Quick connector is compatible with dedicated LED housings
- 5-year limited warranty
- cULus classified for wet locations

#### SPECIFICATION

**Reflector:** One piece, die-cast aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

**Mounting:** Two steel, spring mounting blades allow for easy and secure mounting in most 4" housings.

**Optics:** Nora specified and designed precision-molded lens for optimal lumen output and even distribution. The white polymer lens diffuser evenly distributes the light.

**Retrofit:** Onyx retrofit series includes medium base screw-socket adapter ([NRA-21ISM](#)) for retrofitting into existing medium base downlight housings. GU24 socket adapter is available for use with GU24 housings, must specify [NRA-212SM](#).

#### ELECTRICAL

**Input Voltage:** 120V

**Lumens / Wattage:**

(blank) = 650lm / 10.5W; /9 = 900lm / 14.5W

**Color Temperature:** 3500K, 4000K or 5000K

**Color Rendering Index:** 90+CRI

**Operating Temperature:** 0°C to 45°C

**Dimming:** 5% with electronic low voltage dimmer  
or 10% with 2-wire dimmer

[Click Here](#) or check complete dimmer list at  
[www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under  
"Resources" tab

#### COMPATIBLE HOUSINGS

Onyx reflectors are compatible with most 4" IC and Non-IC housings by Nora and others.

#### Fire Box

- [NFBIC-4LMRATA\\*](#) IC Air-Tight Dedicated LED Firebox
- [NFBIC-427LMRATA\\*](#) Shallow ICAT Dedicated LED Firebox
- [NFBIC-4INCATA](#) IC Air-Tight Line Voltage Firebox

#### New Construction

- [NHIC-4LMRAT\\*](#) IC Air-Tight Dedicated LED
- [NHIC-4LMRAT/277\\*](#) ICAT Dedicated LED, 277V  
(includes step-down transformer)
- [NHICCP-4LMRAT\\*](#) Chicago Plenum Dedicated LED  
(NHICCP-4LMRAT is not compatible with 900lm)
- [NHIC-427LMRAT\\*](#) Shallow IC Air-Tight Dedicated LED  
(NHIC-427LMRAT is not compatible with 900lm)
- [NSIC-401QAT](#) IC Air-Tight Line Voltage
- [NS-401QAT](#) Air-Tight Line Voltage
- [NHIC-4G24AT](#) IC Air-Tight GU24

#### Remodel

- [NHRIC-4LMRAT\\*](#) IC Air-Tight Dedicated LED
- [NHRIC-427LMRAT\\*](#) Shallow IC Air-Tight Dedicated LED  
(NHRIC-427LMRAT is not compatible with 900lm)
- [NSR-404QAT](#) Air-Tight Line Voltage

\* Nora LED Dedicated housings are cULus listed for use only with Nora LED Retrofits.

#### ACCESSORIES

- [NOX-4EYELIDW](#): Round eyelid used to convert round reflector or baffle to half moon wall wash trim.
- [NOX-4OR-W](#): Round oversize ring used to cover ceiling cut-outs up to 5-<sup>3</sup>/<sub>8</sub>".

#### LABELS AND LISTINGS

- cULus classified for Wet Locations
- [5-Year Limited Warranty](#)
- Meets ASTM-E283 Air-Tight requirements
- Certified to the high efficacy requirements of California Title 24 JA8-2022



Type

Project

Catalog No.

Notes

#### PRODUCT IMAGES AND DIMENSIONS





**NOX-432**  
Round Baffle



**NOX-432 / NOX-4EYELIDW**  
White Eyelid



**NOX-432 / NOX-4OR-W**  
White Oversize Ring



### 4" Onyx Round Retrofit Baffle

Lumens / Wattage / Color Temperature

- [NOX-43227WW](#) = 650lm / 10.5W / 2700K (Discontinued, direct replacement: [NOXAC-43227WW/HL](#))
- [NOX-43227WW/9](#) = 900lm / 14.5W / 2700K (Discontinued, direct replacement: [NOXAC-43227WW/HL](#))
- [NOX-43230WW](#) = 650lm / 10.5W / 3000K (Discontinued, direct replacement: [NOXAC-43230WW/HL](#))
- [NOX-43230WW/9](#) = 900lm / 14.5W / 3000K (Discontinued, direct replacement: [NOXAC-43230WW/HL](#))
- [NOX-43235WW](#) = 650lm / 10.5W / 3500K
- [NOX-43235WW/9](#) = 900lm / 14.5W / 3500K
- [NOX-43240WW](#) = 650lm / 10.5W / 4000K
- [NOX-43240WW/9](#) = 900lm / 14.5W / 4000K
- [NOX-43250WW](#) = 650lm / 10.5W / 5000K
- [NOX-43250WW/9](#) = 900lm / 14.5W / 5000K

### Optional Accessories

Description

- NOX-4EYELIDW** = 4" Round Eyelid, White
- NOX-4OR-W** = 4" Round Oversize Ring, White
- NRA-21ISM** = Medium base screw-in socket (included w/ ea)
- NRA-212SM** = Socket adapter for use with GU24 housings

Example: **NOX-43250WW** = 4" Onyx Baffle, 650lm / 10.5W LED, 5000K, White Reflector / White Finish