

WAC LIGHTING

Paloma LED512

9.5W W Track Luminaire

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

System Type & Voltage	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
WHK 277 VAC WTK 120 VAC	LED512	F 36°	27 2700K - 85	850	2105	BK Black PT Platinum WT White
			30 3000K - 85	885	2195	
			35 3500K - 85	910	2259	
			40 4000K - 85	920	2282	
			927 2700K - 90	710	1755	
			930 3000K - 90	735	1821	
		N 24°	27 2700K - 85	685	3152	
			30 3000K - 85	860	3286	
			35 3500K - 85	885	3382	
			40 4000K - 85	895	3417	
			927 2700K - 90	685	2628	
			930 3000K - 90	715	2727	
		S 19°	27 2700K - 85	800	3773	
			30 3000K - 85	835	3832	
			35 3500K - 85	860	4048	
			40 4000K - 85	870	4089	
			927 2700K - 90	670	3145	
			930 3000K - 90	695	3264	

Example: **WHK-LED512F-27-BK**

FEATURES


- High Output COB LED
- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Integral selector to choose between independently controllable track circuits
- Recessed driver hidden within W track
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum with regressed driver and cap ring. Clear glass lens included.
Power:	9.5W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED 3 Step Mac Adam Ellipse
Rated Life:	50000 Hours
Finish:	Electrostatically Powder Coated: Platinum, White, Black
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Dry Location Listed, Title 24 JA8 Compliant



FINISHES:



LINE DRAWING:



WAC LIGHTING

WAC LIGHTING

Paloma LED512
9.5W W Track Luminaire






Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	LENS-16-RED LENS-16-GRN LENS-16-BLU LENS-16-AMB	Colored Lens Colored Lens Colored Lens Colored Lens	Red Green Blue Amber
	LENS-16-FR	Clear/Frosted Lens	Frosted
	LENS-16-SPR	Spread Lens	Spread Lens
	LENS-16-BEL	Beam Elongating Lens	Beam Elongating
	LENS-16-HCL	Honeycomb Louver	Black