R2FRDL-WD

2" FQ - Round Downlight Trimless (Dim-To-Warm)





Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- · Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- 30° shielding angle design for better visual comfort
- Field changeable beam angle with reflectors provided
- · Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 3 1/2"

Accomodates 1/2 "- 1 " ceiling thickness

Finish: Electrostatically powder coated White, Black, Dark

Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed, Energy Star 2.0,

Title 24 JA8-2019 Compliant.

	Model	Beam	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
5" - 234" -	R2FRDL Round Trimless	F 40° W 55°	965 950	1775 1370	WD 3000K-1800K	90	BK DB HZ WT	Black Dark Bronze Haze White

R2FRDL-WD-

Example: R2FRDL-WD-WT (Beam F-40° reflector is pre-installed. Beam W-55° reflector is included.)

Please see next page for housing units (required)

R2FRDL-WD

WAC

2" FQ - Round Downlight Trimless (Dim-To-Warm)

HOUSING (Required)		Model	Power	Emergency Backup
New Construction IC Airtight	5%" 3½"			
	24"MAX 24" MAX 234" H 476" - 1476" - 1776"	R2FRNL	1 15WIC	N/A
Remodel Non-IC	2½"	R2FRRL	1 15W Non-IC	N/A
	Ø5%" 2"			

R2FR -

Example: R2FRNL-1

GLARE CONTROL ACCESSORIES

LENS-11-HCM	Honeycomb Louver
LENS-11P-CRL-BK	Cross Louver

LENS ACCESSORIES

LENS-11	AMB	Amber
	RED	Red
	BLU	Blue
	GRN	Green
	SPR	Spread
	BEL	Beam Elongating