R4FRWT-WD

4" FQ - Round Wall Wash Trim (Dim-To-Warm)





Fixture Type:		
Catalog Numbe	er:	
Project:		

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- 365° horizontal rotation
- · Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Location:

Construction: Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accomodates 1/2 "- 1 " ceiling thickness

Finish: Electrostatically powder coated White, Black, Dark

Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed,

Title 24 JA8-2019 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
5 %" 5 %" 5 %"	R4FRWT Round Trim	A Asym	950	N/A	WD 3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White

R4FRWT-WD-

Example: R4FRWT-WD-WT

*Lumens shown in the table is a reference value for WD trim with 2 housing. Use multiplier table below to determine the output for the other combination.

Multiplier		TRIM		
HOUSING	2	1.00		
	1	0.69		

Example: R4FRWT-WD-WT with 1 housing: 950 lm (Reference Output) x 0.69 (Multiplier) = 655 lm

Please see next page for housing units (required)

waclighting.comHeadquarters/Eastern Distribution CenterCentral Distribution CenterWestern Distribution CenterPhone (800) 526.258844 Harbor Park Drive1600 Distribution Ct1750 Archibald AvenueFax (800) 526.2585Port Washington, NY 11050Lithia Springs, GA 30122Ontario, CA 91761

R4FRWT-WD

WAC

4" FQ - Round Wall Wash Trim (Dim-To-Warm)

HOUSING (Required)		Model	Power		Emergency Backup
New Construction IC Airtight	10" 14%" 14%" 14%" 173%"	R4FBNT		BW IC 9W IC	EM Optional
New Construction Frame-in Non-IC	10" -4%" -1 1434" -1736"	R4FBFT		3W Non-IC 9W Non-IC	EM Optional
Remodel Non-IC	□ 2½" 1 5½" → 1 5½" → 1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	R4FBRT		3W Non-IC 9W Non-IC	N/A

R4FB__-

Example: R4FBNT-2 or R4FBNT-2-EM (with Emergency backup battery)