

# R4FRWT

## 4" FQ - Round Wall Wash Trim



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

### FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 365° horizontal rotation
- Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input** Universal 120-277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-1%  
TRIAC: 100%-1%  
0-10V: 100-1%
- Light Source:** High output 3-step Mac Adam Ellipse COB  
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accommodates 1/2" - 1" ceiling thickness
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed, Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	<b>R4FRWT</b> Round Trim	A Asym	1845	N/A	<b>927</b> 2700K	90	<b>BK</b> <b>DB</b> <b>HZWT</b> <b>WT</b>	Black Dark Bronze Haze/White White
			1940	N/A	<b>930</b> 3000K	90		
			1980	N/A	<b>935</b> 3500K	90		

### R4FRWT-\_\_-\_\_

Example: **R4FRWT-930-WT**

\*Lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier		TRIM		
		927	930	935
HOUSING	4	0.95	1.00	1.02
	3	0.84	0.88	0.90
	2	0.65	0.68	0.70
	1	0.45	0.47	0.48

Example: **R4FRWT-930-WT** with 1 housing: 1940 lm (Reference Output) x 0.47 (Multiplier) = 910 lm

Please see next page for housing units(required)

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center




1750 Archibald Avenue

Ontario, CA 91761

# R4FRWT

## 4" FQ - Round Wall Wash Trim



HOUSING (Required)	Model	Power	Emergency Backup
<p>New Construction IC Airtight</p> 	<b>R4FBNT</b>	<p><b>1</b> 13W IC  <b>2</b> 19W IC  <b>3</b> 25W IC  <b>4</b> 28W Non-IC</p>	<b>EM Optional</b>
<p>New Construction Frame-in Non-IC</p> 	<b>R4FBFT</b>	<p><b>1</b> 13W Non-IC  <b>2</b> 19W Non-IC  <b>3</b> 25W Non-IC  <b>4</b> 28W Non-IC</p>	<b>EM Optional</b>
<p>Remodel Non-IC</p> 	<b>R4FBRT</b>	<p><b>1</b> 13W Non-IC  <b>2</b> 19W Non-IC  <b>3</b> 25W Non-IC  <b>4</b> 28W Non-IC</p>	N/A

### R4FB \_\_\_\_ - \_\_\_\_

Example: **R4FBNT-3** or **R4FBNT-3-EM** (with Emergency backup battery)

waclighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91761