R4FSAT 4″ FQ - Square Adjustable Trim





PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- 0-45° vertical tilting and 365° horizontal rotation
- Center beam alignment retained throughout adjustment range
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

Fixture Type:	
Catalog Number:	

Project:

Location:

SPECIFICATIONS					
Construction:	Durable die-cast aluminum construction				
Input	Universal 120-277V AC 50/60 Hz				
Dimming:	Electronic Low Voltage (ELV): 100%-1% TRIAC: 100%-1% 0-10V: 100-1%				
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70				
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accomodates 1/2 "- 1 " ceiling thickness				
Finish:	Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.				
Standards:	ETL & CETL Damp Location Listed, Energy Star 2.0, Title 24 JA8 Compliant.				

Model	Model	В	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
		N F W	27° 40° 50°	1595 1515 1590	5110 3320 2995	927 2700K	90		
5%"	R4FSAT Square Trim	N F W	27° 40° 50°	1680 1595 1670	5375 3495 3150	930 <i>3000K</i>	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
⊢ 3" – ⊢ 5 ¼" —		N F W	27° 40° 50°	1715 1625 1705	5485 3565 3215	935 3500K	90		Winte

R4FSAT-__-

Example: R4FSAT-927-BK (Beam N-27° reflector is pre-installed. Beams F-40° and W-50° reflectors are included.)

* Lumens and CBCP are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier 927		TR		
		927	930	935
	4	0.95	1.00	1.02
HOUSING	3	0.84	0.88	0.90
licosing	2	0.65	0.68	0.70
	1	0.45	0.47	0.48

Example: **R4FSAT-930-BK** N-27° beam in **1** housing: 1680 lm (Reference Output) x 0.47 (Multiplier) = 790 lm

5375 CBCP (Reference Output) x 0.47 (Multiplier) = 2525 CBCP

Please see next page for housing units(required)

waclighting.com	Headquarters/Eastern Distribution Center
Phone (800) 526.2588	44 Harbor Park Drive
Fax (800) 526.2585	Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91761

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JAN 2023



HOUSING (Required)		Model	Power	Emergency Backup
New Construction IC Airtight	$\begin{bmatrix} & & & & & \\ & & & & \\ & & & & \\ & & & & \\ 10'' & & & & \\ & & & & \\ 10'' & & & & \\ & & & & \\ & & & & \\ & & & &$	R4FBNT	1 13W IC 2 19W IC 3 25W IC 4 28W Non-IC	EM Optional
New Construction Frame-in Non-IC	$ \begin{array}{c} \begin{array}{c} 1\\ 3\%''\\ 1 \end{array} $	R4FBFT	1 13W Non-IC 2 19W Non-IC 3 25W Non-IC 4 28W Non-IC	EM Optional
Remodel Non-IC		R4FBRT	1 13W Non-IC 2 19W Non-IC 3 25W Non-IC 4 28W Non-IC	N/A

R4FB___-

Example: R4FBNT-3 or R4FBNT-3-EM (with Emergency backup battery)

GLARE CONTROL ACCESSORIES

LENS-16-HCM	Honeycomb Louver
LENS-16P-CRL-BK	Cross Louver

LENS ACCESSORIES

LENS-16	АМВ	Amber
	RED	Red
	BLU	Blue
	GRN	Green
	SPR	Spread
	BEL	Beam Elongating

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91761

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JAN 2023