## **R4FSWT-WD** 4" FQ - Square Wall Wash Trim (Dim-To-Warm)





Fixture Type:	
Catalog Number:	

Project:

Location:

#### **PRODUCT DESCRIPTION**

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

#### FEATURES

- Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

SPECIFICATIONS				
Construction:	Durable die-cast aluminum construction			
Input	Universal 120-277V AC 50/60 Hz			
Dimming:	Electronic Low Voltage (ELV): 100%-1% TRIAC: 100%-1% 0-10V: 100-1%			
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70			
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accomodates 1/2 "- 1 " ceiling thickness			
Finish:	Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.			
Standards:	ETL & cETL Wet Location Listed, Title 24 JA8-2019 Compliant.			

 Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
<b>R4FSWT</b> Square Trim	A Asym	950	N/A	<b>WD</b> 3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White

## R4FSWT-WD-

### Example: R4FSWT-WD-WT

\*Lumens shown in the table is a reference value for WD trim with 2 housing. Use multiplier table below to determine the output for the other combination.

Multiplier		TRIM			
HOUSING	2	1.00			
	1	0.69			

Example: R4FSWT-WD-WT with 1 housing: 950 lm (Reference Output) x 0.69 (Multiplier) = 655 lm

Please see next page for housing units (required)

waclighting.com Phone (800) 526.2588 44 Harbor Park Drive Fax (800) 526.2585 Port Washington, NY 11050

Headquarters/Eastern Distribution Center

**Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91761

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JAN 2022

# **R4FSWT-WD** 4" FQ - Square Wall Wash Trim (Dim-To-Warm)



HOUSING (Required)		Model	Power		Emergency Backup
New Construction IC Airtight	$\begin{bmatrix} & & & & \\ & & & & \\ & & & & \\ & & & & $	R4FBNT	1 2	13W IC 19W IC	<b>EM</b> Optional
New Construction Frame-in Non-IC	$\begin{bmatrix} 1 \\ 3 \\ 3 \\ 4 \end{bmatrix}^{n}$	R4FBFT	1 2	13W Non-IC 19W Non-IC	<b>EM</b> Optional
Remodel Non-IC		R4FBRT	1 2	13W Non-IC 19W Non-IC	N/A

## R4FB\_\_\_-

Example: R4FBNT-2 or R4FBNT-2-EM (with Emergency backup battery)

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91761