## R4FSWT

## 4" FQ - Square Wall Wash Trim





#### PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

#### **FEATURES**

- Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

Fixture Type:
Catalog Number:
Project:
Location:

#### **SPECIFICATIONS**

Construction: Durable die-cast aluminum construction
Input Universal 120-277V AC 50/60 Hz
Dimming: Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

**Light Source:** High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accomodates 1/2 "- 1 " ceiling thickness

Finish: Electrostatically powder coated White, Black, Dark

Bronze. Enamel coated Haze.

**Standards:** ETL & cETL Wet Location Listed,

Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
			1770	N/A	<b>927</b> 2700K	90		
5%"	<b>R4FSWT</b> Square Trim	A Asym	1865	N/A	<b>930</b> <i>3000K</i>	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
⊢ 3"			1900	N/A	<b>935</b> <i>3500K</i>	90		

### R4FSWT-\_\_-

Example: R4FSWT-930-WT

\*Lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier		TR		
		927	930	935
HOUSING	4	0.95	1.00	1.02
	3	0.84	0.88	0.90
	2	0.65	0.68	0.70
	1	0.45	0.47	0.48

Example: R4FSWT-930-WT with 1 housing: 1865 lm (Reference Output) x 0.47 (Multiplier) = 875 lm

Please see next page for housing units (required)

waclighting.comHeadquarters/Eastern Distribution CenterCentral Distribution CenterWestern Distribution CenterPhone (800) 526.258844 Harbor Park Drive1600 Distribution Ct1750 Archibald AvenueFax (800) 526.2585Port Washington, NY 11050Lithia Springs, GA 30122Ontario, CA 91761

## **R4FSWT**

# 4" FQ - Square Wall Wash Trim



HOUSING (Required)		Model	Trim	Power	Emergency Backup
New Construction IC Airtight	5 %"  10"  14%"  14%"  17%"	R4FBNT		1 13W IC 2 19W IC 3 25W IC 4 28W Non-IC	<b>EM</b> Optional
New Construction Frame-in Non-IC	10"	R4FBFT		1 13W Non-IC 2 19W Non-IC 3 25W Non-IC 4 28W Non-IC	<b>EM</b> Optional
Remodel Non-IC	2 ½	R4FBRT		1 13W Non-IC 2 19W Non-IC 3 25W Non-IC 4 28W Non-IC	N/A

R4FB\_\_\_-

Example: R4FBNT-3 or R4FBNT-3-EM (with Emergency backup battery)