

2" INGROUND - SHROUD

2111

WAC


LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:



PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire for up, down, side light applications.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fi xtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring clip, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

ORDERING NUMBER

		Color Temp	Finish
2111	Shroud	27 2700K	BS Bronzed Stainless Steel
		30 3000K	SS Stainless Steel

2111-30_____

Example: 2111-30SS

2" INGROUND - SHROUD

2111

WAC

LANDSCAPE LIGHTING

Magnetic Transformers



*Stainless Steel, 12-15V output,
IP65 rated, UL 1838 listed
See transformer spec sheet for
details and its accessories*

- 9075-TRN-SS**
75W Max
- 9150-TRN-SS**
150W Max
- 9300-TRN-SS**
300W Max
- 9600-TRN-SS**
600W Max

2" Concrete Pour Kit



*For installation in concrete.
Use with a 4" outdoor rated junction box
and a trade size 2" schedule 80 PVC pipe*

2000-CON-PVC

TESTED MAGNETIC LOW VOLTAGE (MLV) DIMMERS

Luminaire	Dimmer					
	Manufacturer	Family	Model	Power Rating	Range*	Note
2111	Shroud	Diva	DVLV-600	600W	20% - 100%	
		Skylark	SLV-600P	600W	15% - 100%	Best performance
		Skylark	S-10P	1000W		Not recommended

**Low end of this range is determined by output current which may not directly translate to the perceived light output*

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.