

2" SURFACE INDICATOR SINGLE IRECTIONAL

2591

WAC

LANDSCAPE LIGHTING





Fixture Type:

Catalog Number:

Project:

Location:



PRODUCT DESCRIPTION

LED Landscape surface mount indicator luminaire for both soft and hard ground applications. The indicator light is perfect for outdoor applications, including wells and ponds, decks and patios, inground, as well as ceiling and wall applications.

FEATURES

- Slim low profile design-surface mount installation
- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- 10' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmer

SPECIFICATIONS

Input:	9 - 15VAC (Transformer is required)
Power:	2.8W / 3.2 VA (Use VA value for sizing the transformer and calculate voltage drop.)
Brightness:	7lm
Beam Angle:	110°
CRI:	85
Rated Life:	60,000 hours

ORDERING NUMBER

		Color Temp	Finish	
2591	<i>Single Directional</i>	27 30	2700K 3000K	BS SS <i>Bronzed Stainless Steel Stainless Steel</i>

2591-30_____

Example: **2591-30SS**

2" SURFACE INDICATOR SINGLE IRECTIONAL

2591

WAC
LANDSCAPE LIGHTING

Magnetic Transformers



*Stainless Steel, 12-15V output,
IP65 rated, UL 1838 listed
See transformer spec sheet for
details and its accessories*

2" Concrete Pour Kit

9075-TRN-SS
75W Max

9150-TRN-SS
150W Max

9300-TRN-SS
300W Max

9600-TRN-SS
600W Max