Fixture Type:

Catalog Number:

Project:

Location:

WAC LIGHTING

Endurance™ Brick Lights

Opal Step And Wall Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
❍ WL-5105 120 VAC	❍ 3000K 90	110	❍ ABK Architectural Black ❍ ABZ Architectural Bronze ❍ AGH Architectural Graphite ❍ AWT Architectural White

Example: **WL-5105-30-ABK**

DESCRIPTION

Designed for integration into brick walls or vertical risers. The energy-efficient Endurance™ LED Brick Light features a die-cast aluminum housing and integrated LED light engine with a heat resistant opal glass diffuser for a glare-free even spread of light, making outdoor areas safer and more secure.

FEATURES

- Frosted tempered glass lens for even illumination
- Factory sealed LED light engine
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast aluminum (K-Alloy)
Power:	5.5W
Input:	120 VAC,50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
Rated Life:	80,000 Hours
Mounting:	Mortar into masonry, screw into wood walls, or retrofit into existing brick light installations, Can be mounted on wall vertically or horizontally
Cut Out:	3 1/4" x 8"
Finish:	Electrostatically Powder Coated: Architectural Black, Architectural Bronze, Architectural Graphite, Architectural White
Operating Temp:	-40°F to 122°F (-40°C to 50°C)
Standards:	ETL, cETL, Wet Location Listed, IP66, ADA

FINISHES:

Architectural Black | Architectural Bronze | Architectural Graphite | Architectural White

LINE DRAWING



REPLACEMENT PARTS

5005-30 - Replacement Light Engine 3000K
5005-PLATE - Light Engine Mounting Plate
5105-COV-ABK - Opal Cover Plate ABK
5105-COV-ABZ - Opal Cover Plate ABZ
5105-COV-AGH - Opal Cover Plate AGH
5105-COV-AWT - Opal Cover Plate AWT

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. January 2026