

# WAC LIGHTING

## Step Light with Photocell

Fixture Type:

Catalog Number:

Project:

Location:

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-LED202 120 VAC	Amber 0 3000K 90	65 65	BK Black on Aluminum BN Brush Nickel on Aluminum BZ Bronze on Aluminum SS Stainless Steel WT White on Aluminum

Example: **WL-LED202-30-BK**

### FEATURES


- Options in die-cast brass or 316 marine-grade stainless steel
- Fits into 2"×4" J-Box with minimum inside dimensions of 3"×2"×2"
- No driver needed
- No heat radiation
- Low profile, flush to wall aesthetics with no visible hardware
- Balanced lighting, free of shadows with minimum glare
- Integrated photocell for energy saving
- Driver concealed within the fixture
- 5 Year warranty




### SPECIFICATIONS

Construction	Stainless Steel, Corrosion resistant aluminum alloy
Power:	2W
Input:	120 VAC, 50/60Hz
Light Source:	Integrated LED, 3 Step Mac Adam Ellipse
Lens:	Tempered Glass
Rated Life:	54,000 Hours
Finish:	Enamel Coated Black on Aluminum, Enamel Coated White on Aluminum, Enamel Coated Brush Nickel on Aluminum, Enamel Coated Bronze on Aluminum, Stainless Steel Stainless Steel
Operating Temp:	-40°F to 122°F (-40°C to 50°C)
Standards:	ETL, cETL, Wet Location Listed, IP66, ADA

### FINISHES:



Black on  
Aluminum



Bronze on  
Aluminum



Brush Nickel  
on Aluminum



Stainless  
Steel



White on  
Aluminum

### LINE DRAWING

