

WAC LIGHTING

WL-LED120

Step And Wall Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-LED120 120 VAC	Amber 90 3000K 90	36 36	BK Black on Aluminum
WL-LED120F 277 VAC	Amber 90 3000K 90	36 36	BZ Bronze on Aluminum WT White on Aluminum

Fixture Type:

Catalog Number:

Project:

Location:

Example: **WL-LED120-AM-BK**

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

FEATURES

- Louvered design offers shielded illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast corrosion resistant aluminum alloy
Power:	3W, 3.5W
Input:	120 VAC, 277 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
Rated Life:	50,000 Hours
Mounting:	Fits into 2" x 4" J-Box with minimum inside dimensions of 3"L x 2"W x 2.5"D
Finish:	Enamel Coated Bronze on Aluminum, Enamel Coated White on Aluminum, Enamel Coated Black on Aluminum
Operating Temp:	-40°F to 104°F (-40°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, IP66, ADA, Title 24 JA8 Compliant

REPLACEMENT PARTS

REF-R4-F - Flood Reflector

REF-R4-N - Narrow Flood Reflector



FINISHES:



LINE DRAWING

