

WAC LIGHTING

WL-LED130

Step And Wall Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-LED130 120 VAC	Amber 90 3000K 90	40 40	BK Black on Aluminum BZ Bronze on Aluminum
WL-LED130F 277 VAC	Amber 90 3000K 90	40 40	SS Stainless Steel WT White on Aluminum

Example: **WL-LED130-AM-BK**

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.



FEATURES

- Diffuse tempered glass provides even illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- Can be mounted vertically or horizontally
- 5 year warranty


SPECIFICATIONS

Construction	Cast 316 marine grade stainless steel, Die-cast corrosion resistant aluminum alloy
Power:	3W, 3.5W
Input:	120 VAC, 277 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
Rated Life:	50,000 Hours
Mounting:	Fits into 2" x 4" J-Box with minimum inside dimensions of 3" L x 2" W x 2.5" D
Finish:	Enamel Coated White on Aluminum, Stainless Steel, Stainless Steel, Enamel Coated Bronze on Aluminum, Enamel Coated Black on Aluminum
Operating Temp:	-40°F to 104°F (-40°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, IP66, ADA, Title 24 JA8 Compliant

FINISHES:



LINE DRAWING



REPLACEMENT PARTS

W-4071-130-BK - LED130 Cover Plate BK
W-4071-130-BZ - LED130 Cover Plate BZ
W-4071-130-SS - LED130 Cover Plate SS
W-4071-130-WT - LED130 Cover Plate WT