DECK & PATIO - TRIANGLE

3021

WAC
LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:



PRODUCT DESCRIPTION

Deck and patio light with superb forward-throw light distribution

FEATURES

- IP66 rated, Protected against powerful water jets
- 6' lead wire included
- Translucent lens provides for uniform diffused light output
- Solid diecast brass or corrosion resistant aluminum alloy
- ADA compliant
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Input: 9-15VAC (Transformer is required)
Power: 2.8W / 4.6VA (Use VA value for sizing the transformer and calculate voltage drop.)
Brightness: 60 lm
CRI: 90+
Rated Life: 50,000 hours

ORDERING NUMBER

		Color Temp		Finish	
3021	*Triangle*	**27**	*2700K*	**BBR**	*Bronze on Brass*
		30	*3000K*	**BK**	*Black on Aluminum*
				BZ	*Bronze on Aluminum*
				WT	*White on Aluminum*

3021-_____

Example: **3021-30BZ**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104

West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program.

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed
See transformer spec sheet for details and its accessories

9075-TRN-SS	**9150-TRN-SS**	**9300-TRN-SS**	**9600-TRN-SS**
75W Max	*150W Max*	*300W Max*	*600W Max*

TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS

Luminaire	Dimmer					
	Manufacturer	Family	Model	Power Rating	Range*	Note
3021	*Lutron*	*Diva*	*DVLV-600*	*600W*	*33% - 100%*	*Output maxes at 50% dimming level*
		Skylark	*SLV-600P*	*600W*	*28% - 100%*	*Output maxes at 50% dimming level*
		Skylark	*S-10P*	*1000W*		*Not recommended*

*Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.