


SQUARE


ROUND

OPTIONAL POSTS

DIMENSIONS:



SQUARE



ROUND

- WMS-S-50K-BR** **WMS-S-50K-WH**
- WMS-S-30K-BR** **WMS-S-30K-WH**
- WMS-R-50K-BR** **WMS-R-50K-WH**
- WMS-R-30K-BR** **WMS-R-30K-WH**

LED WALL/STEP LIGHTS

Ideal for general site lighting, alleys, loading docks, doorway, pathway, and parking areas.

ELECTRICAL SPECIFICATIONS:

- Voltage: 100~277 VAC, 50/60 Hz
- Wattage: 6 W
- Power factor: 0.95
- Efficacy: 80 LM/W

HOUSING SPECIFICATIONS:

- Die-cast aluminum with powder coat finish (Dark Bronze or White)
- Polycarbonate front housing
- vandal resistance
- Four 1/2" HUBS
- Operating temperature: -40°F to 104°F
- Lifespan: 70,000 hr.
- IP Rating: IP54

CERTIFICATIONS: UL



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP	SHAPE
WMS-S-50K-BR	6W	100~277 VAC	480LM	5000K	SQUARE
WMS-S-30K-BR	6W	100~277 VAC	480LM	3000K	SQUARE
WMS-R-50K-BR	6W	100~277 VAC	480LM	5000K	ROUND
WMS-R-30K-BR	6W	100~277 VAC	480LM	3000K	ROUND
WMS-S-50K-WH	6W	100~277 VAC	480LM	5000K	SQUARE
WMS-S-30K-WH	6W	100~277 VAC	480LM	3000K	SQUARE
WMS-R-50K-WH	6W	100~277 VAC	480LM	5000K	ROUND
WMS-R-30K-WH	6W	100~277 VAC	480LM	3000K	ROUND

OPTIONAL POSTS:

MODEL	DESCRIPTION
WMS-POST1-18	18" One side post for WMS & LWA-12W series, Dark Bronze Finish
WMS-POST2-18*	18" Two side post for WMS & LWA-12W series, Dark Bronze Finish
WMS-POST1-36	36" One side post for WMS & LWA-12W series, Dark Bronze Finish
WMS-POST2-36*	36" Two side post for WMS & LWA-12W series, Dark Bronze Finish

LIGHTING SPECIFICATIONS:

- Lens: Prismatic Lens
- LED Chip: Lumileds LEDs
- Total lumens: 480LM
- Color temperature: 5000K/3000K
- Color rendering index: >80
- Beam Angle: 110°X65°

WARRANTY: 7 years

