

WAX SERIES

Outdoor Lighting

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

WAX-50-80W-MCTP-SIL


MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



Ideal for general site lighting, alleys, loading docks, doorway, pathway, and parking areas. Great for use with motion sensors or another instant on/off controls.

14" (W) x 12 8/9" (H) x 5 1/4" (D)

Features

- High Light Transmittance, Anti-UV and Fire Resistant PC Lens
- Two 1/2" Knockouts on Each Side
- Die-Cast Aluminum With Powder Coat Finish
- 7-Year Warranty
- Multi CCT and Power (Switches are inside fixture)

Technical Specifications

Electrical:

- Voltage: 120-277V AC 60Hz
- Wattage: 50W/65W/80W
- Power Factor: >0.9
- THD: <20%
- Efficacy: 140 LPW

Mechanical:

- Die-Cast Aluminum With Powder Coat Finish
- High Light Transmittance, Anti-UV and Fire Resistant Shatterproof PC Lens
- DC Button Photocell with ON/OFF switch Included
- Light Head Can Be Adjusted From 0° to 90°
- Full Cutoff, Dark Sky Compliant
- Two 1/2" Knockouts on Each Side
- Operating Temperature: -40°F -113°F
- 7-Year Warranty
- IP65, Suitable For Wet Location

Lighting:

- Dimming: 0~10V Dimmable
- Multi CCT and Power (Switches are inside fixture)
- Lumileds 2835, High CRI.
- Total Lumens: 11200LM Max
- Color Temperatures: 3000K/4000K/5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: H127° x V85°
- Rated life: 70,000 Hrs

Applications:

- Entrance Lighting
- Courtyard Lighting
- Industrial Lighting
- Outdoor Landscape Lighting
- Building The hotel
- Wall Lighting Area And So On





Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com |




WG-ZY-24-2Z

Photometrics: WAX-50-80W-MCTP-SIL



BUD Rating: B3-U3-G3



Area 75'x 75' Mounting Height: 8'

Other Views:



Side View



Front View



Bottom View

Performance Table: WAX-50-80W-MCTP-SIL

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
WAX-50-80W-MCTP-SIL	50W	120~277V	7000LM	3000K 4000K 5000K	B3-U3-G3	140
	65W		9100LM			
	80W		11200LM			

Sample Ordering

Model	Min.	Wattage	Color Temp.	Color				
WAX	-	50	-	80W	-	MCTP	-	SIL

Factory-Installed Option:

Blank = No Option For Accessories
 OPT-EM-WAX-80 = INTERNAL EMERGENCY BACK UP BATTERY
 OPT-SEN-3MRLV-5 = PROGRAMMABLE MICROWAVE SENSOR
 OPT-WP-480V = CHANGE VOLTAGE TO 480V
 OPT-CLR-85(BK/GR/SR/WH) = PAINT
 OPT-CLR-MC (260 SET UP PRICE FEE PER PROJECT) = PAINT
 OPT-TRS-T20 = TAMPER RESISTANT

FACTORY-INSTALLED OPTION:



OPT-EM-WAX-80



OPT-SEN-3MRLV-5




COLOR CHART: * Choose from one of our Premium Colors with no set-up fee.

Gloss:



Hammer:



Texture:



Vein:

