

GPX SERIES Outdoor Lighting

GPX-18-60W-MCTP-A1

POST DISK LIGHT WITH SINGLE ARM

MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)



SINGLE ARM

Ideal for airports, auto dealerships, corporate offices, education, government, healthcare, industrial warehouses, municipal parking, gas stations, convenient stores, recreation and public venues, restaurants, hospitality, retail and grocery stores.

WESTGATE


THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



15 3/4" (W) X 21" (H)
Inside Diameter: 2 3/4"

Features

- Aluminum Housing ,Outdoor Powder Coated
- 7-Year Warranty
- Multi CCT and Power: Selectable Switch Inside Of The Fixture

Technical Specifications

Electrical:

- Voltage: 100-277V AC 50/60Hz
- Wattage: 18W/30W/45W/60W
- Power Factor: 0.95
- Efficacy: 150LM/W

Mechanical:

- Aluminum Housing , Outdoor Powder Coated
- Single Arm Fits On 2-3/4" Poles
- For 2-3/8" OD Pole/Pipe
- Programmable Bi-Level Motion Sensor & Emergency Backup Options
- EPA Rating: 2.78 Square Feet
- Operating Temperature: -86°F~122°F
- IP Rating: IP66, Suitable for Wet Locations
- 7-Year Warranty

Lighting:

- Multi CCT and Power: Selectable Switch Inside Of The Fixture
- Dimmable: 0~10V Dimming
- LED: SMD 3030
- Total Lumens: 9000LM Max.
- Color Temperature: 3000K/4000K/5000K
- Color Rendering index: >70
- Beam Angle: Type V (150° X 150°)
- Lifespan: 70000 Hrs.

Applications:

- Ideal For Garden, Amusement Park, Residential Quarter, Industrial Park And Pedestrian street.




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com




WG-04062022

Photometrics: GPX-18-60W-MCTP-A1



BUD Rating: B1-U1-G0



20W 5000K, Area 55'x 75' Mounting Height: 9'

Other Views:



Single Arm Mount



Lens View



Top View

Performance Table: GPX-18-60W-MCTP-A1

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
GPX-18-60W-MCTP-A1	18W 30W 45W 60W	120-277V	2700LM 4500LM 6750LM 9000LM	3000K 4000K 5000K	B1-U1-G0	150

Sample Ordering

Model	Min. Watt	Max. Watt	Color Temp.	Mount
GPX - 18 - 60W - MCTP - A1				

Factory Installed Options:

Blank = No Option
 OPT-EM-OD2INT = INTERNAL EMERGENCY BACK UP BATTERY
 OPT-3MPC = MICROWAVE PHOTOCELL
 OPT-CLR-95(BK/GR/SR/WH) = COLOR PAINT
 OPT-SEN-3MR-3 = BI-LEVEL MICROWAVE SENSOR
 WEC-8RC = REMOTE CONTROL
 OPT-WP-480V = 480V OPTION
 OPT-GPX-LENS-TYPE2S = FACTORY- INSTALLED TYPE 2 LENS
 OPT-GPX-LENS-TYPE3S = FACTORY- INSTALLED TYPE 3 LENS
 OPT-GPX-LENS-FL = FACTORY- INSTALLED FROSTED GLASS LENS

FACTORY INSTALLED OPTIONS:



COLOR CHART: * Choose from one of our Premium Colors with no set-up fee.

Gloss:



SILVER METALLIC
70 GLOSS
T357-GR105



SILVER METALLIC
30 GLOSS
T353-GR06



DARK RED 90
GLOSS
P009-RD02



INTERNATIONAL
ORANGE 90
GLOSS
T009-OG26



SAFETY ORANGE
90 GLOSS
T009-OG01



YELLOW 90
GLOSS
T009-YL14



YELLOW 90
GLOSS
T009-YL01



TRAFFIC GREEN
70 GLOSS
T007-GN16



GREEN 70 GLOSS
T007-GN13



GREEN 60 GLOSS
C006-GN03



BLUE 90 GLOSS
T009-BL01



DARK BLUE 80
GLOSS
T008-BL20



RAL 8028 TERRA
BROWN 90 GLOSS
C209-BR358

Hammer:




WHITE HAMMER
T013-WH09



BEIGE HAMMER
T013-BG38



GREY HAMMER
C013-GR08



SILVER
HAMMERTONE
T064-GR05




BLACK HAMMER
T013-BK62



RED HAMMER
T013-RD15



GREEN HAMMER
T013-GN220



BLUE HAMMER
T013-BL468



BRONZE HAMMER
T012-BR161

Texture:



WHITE TEXTURE
C031-WH120



FLINT GRAY
TEXTURE
T243-GR522




BLACK TEXTURE
C241-BK109



RED TEXTURE
T241-RD129



BLUE TEXTURE
C241-BL544




OIL RUBBED
BRONZE TEXTURE
T291-BR251


Vein:



BLACK/WHITE
VEIN
T075-WH34



SILVER VEIN
T375-BK26



COPPER VEIN
EXTERIOR
T075-BK211



GOLD VEIN
T375-BK10



COPPER VEIN
T375-BK07

