

# WSX SERIES Outdoor Lighting

WSO-20-40W-MCTP-HA

HORIZONTAL ARM

**MCTP** Multi Color Temperature & Multi Power/Wattage (Selectable)

**WESTGATE**  
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!




LED Seaside Outdoor Wall Lantern with aluminum housing & powder-coated finish, acrylic diffuser. Ideal for general site lighting, residential buildings, doorway, pathway and parking areas.

Customer Name: \_\_\_\_\_

Project Name: \_\_\_\_\_

Note: \_\_\_\_\_

Type: \_\_\_\_\_



10 1/4"(W) x 10 2/3"(H) x 11 1/9"(D)

## Features

- Aluminum Housing and Steel Back Plate
- White Glass Lens
- 7-Year Warranty
- Multi CCT Power Switch is Inside Fixture

## Technical Specifications

### Electrical:

- Voltage: 120V AC 60Hz
- Wattage: 20W/30W/40W
- Power Factor: >0.90
- Efficacy: 100 LPW

### Mechanical:

- Aluminum Housing and Steel Back Plate
- White Glass Lens
- Operating Temperature: -4°F to 104°F
- Wet Location
- 7-Year Warranty
- IP42, Suitable for outdoor use

### Lighting:

- Total Lumens: 4000LM Max.
- Color Temperatures: 3000K/4000K/5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 90° x 110°
- Rated life: 70,000 Hrs

### Applications:

- LED Seaside Outdoor Wall Lantern with aluminum housing & powder-coated finish, acrylic diffuser. Ideal for general site lighting, residential buildings, doorway, pathway and parking areas.





Phone: (877) 805-2252 | Fax: (877) 805-2252  
www.westgatemfg.com




WG-07/21/2022

**Photometrics:** WSO-20-40W-MCTP-HA



BUD Rating: B2-U1-G1



**Other Views:**



Side View



Back View

**Performance Table:** WSO-20-40W-MCTP-HA

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
WSO-20-40W-MCTP-HA	20W 30W 40W	120V	2000LM 3000LM 4000LM	3000K 4000K 5000K	B2-U1-G1	100

**Sample Ordering**

**Model Min. Watt Max. Watt Color Temp. Housing**

WSO - 20 - 40W - MCTP - HA

