

SFX-G12 SERIES

COMMERCIAL OUTDOOR LIGHTING
 SFX-G12AD-500-750W-50K-480V

G12 ADJUSTABLE DISTRIBUTION ANGLE STADIUM LIGHT





Main View



Side View



Back View



Technical Drawing: 19" (H) x 19.7" (W) x 22.9" (D)

The SFX-G12AD-500-750W-50K-480V is the highest-output model in the G12 Adjustable Distribution Angle Stadium Light series, engineered for large sports facilities, high-mast lighting and wide-area commercial outdoor applications. The fixture provides selectable 500W / 600W / 750W power, 200-480 VAC input, 0-10V dimming and adjustable 30° / 40° / 50° / 60° beam distribution for precise project layout flexibility. Its IP66 wet location rated die-cast aluminum housing, Lumileds LED system and integral sensor receptacle deliver durable, high-output performance for demanding stadium, plaza, airport, shipyard and wharf lighting installations.

Customer Name:

Project Name:

Note:

Type:

FEATURES:

- UL/cUL listed
- 480V high-voltage model for commercial and sports lighting applications
- Field-selectable wattage for maximum project flexibility
- Adjustable 30° / 40° / 50° / 60° beam distribution
- Highest-output model in the G12AD series
- Integral sensor receptacle for control-ready applications
- Optional Zhaga receptacle
- Optional 10kV / 20kV surge protection
- Designed for stadiums, gymnasiums, plazas, high-mast lighting, airports, shipyards and wharf applications
- Warranty: 5 years

SPECIFICATIONS:

ELECTRICAL

- Power selectable: 500W / 600W / 750W
- Wattage adjustable from 25% to 100%
- Input voltage: 200-480 VAC, 50/60Hz
- 0-10V dimming
- Power factor: ≥ 0.9
- THD: $\leq 20\%$
- Flicker: $< 5\%$
- 6kV driver surge protection, L/N-PE and L-N
- Optional 10kV / 20kV surge protection
- Integral sensor receptacle
- Optional Zhaga receptacle
- Operating temperature: -40°F to 122°F

LIGHTING

- 5000K color temperature
- Lumens: up to 127,500 LM
- Efficacy: 155 LM/W listed in vendor data
- Beam performance: 150 LM/W at 30°, 170 LM/W at 40°, 165 LM/W at 50°, 155 LM/W at 60°
- Adjustable beam angle: 30° / 40° / 50° / 60°
- CRI: > 70
- Lumileds SMD2835 LEDs
- LED quantity: 1800 pcs
- BUG rating: B5-U0-G5
- NEMA 4 distribution standard
- Optional NEMA 5 distribution
- PC optical lens

MECHANICAL

- Die-cast aluminum housing
- Black finish
- IP66 wet location rated
- Adjustable mounting bracket
- Fixture size: 18.8" L x 19.1" W x 15.3" D
- Fixture weight: 34.23 lbs
- EPA: 2.5 ft²
- Package quantity: 1 piece

PERFORMANCE TABLE

MODEL NO.	WATTAGE	VOLTAGE	LUMEN	COLOR TEMP.	LPW
SFX-G12AD-500-750W-50K-480V	500W 600W 750W	480V	77500LM 93000LM 116250LM	5000K	155