

# DLS SERIES Residential Lighting

DLS6-MCT-BN

**WESTGATE**  
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!




Customer Name: \_\_\_\_\_

Project Name: \_\_\_\_\_

Note: \_\_\_\_\_

Type: \_\_\_\_\_



Disk lights have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.

## Features

- Die-cast Aluminum. Powder-Coated
- Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Wet Location Performance
- Closed Cell Neoprene Foam Gasket
- Multi CCT (Selectable Switch on LED Board Under the Lens)

## Technical Specifications

### Electrical:

- Voltage: 120V AC
- Power Factor: >0.90
- Wattage: 15W
- Efficacy: 67 LPW

### Mechanical:

- Brushed Nickel Finish
- Die-cast Aluminum. Powder-Coated
- Gasket: Closed Cell Neoprene Foam Gasket
- Fits on 4"Octagonal (4O) or 3"Octagonal (3O) Electrical Boxes
- Recessed Mounting Kit Included for Recessed/Retrofit Installation
- Maximum Ambient Temperature: 104°F
- Rated life: 50,000 hrs

### Lighting:

- Lens: White Translucent Acrylic
- LED: Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Wet Location Performance
- Dimming: TRIAC Dimming (Using Standard TRIAC LED Dimmers)
- Total Lumens: 1000LM
- Color Temperatures: 3000K/ 4000K/ 5000K
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- Color Rendering Index: CRI ≥ 90
- 5-Year Warranty

### Applications:

- Disk lights have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

### Other Models:

- 15W | 1000LM | DLS6-MCT • 15W | 1000LM | DLS6-MCT-BR





Phone: (877) 805-2252 | Fax: (877) 805-2252  
www.westgatemfg.com |




WG-05202022

## Photometrics: DLS6-MCT-BN



BUG Rating: B1-U2-G1



Simulation Based on 4000K Area 35'x 35' Mounting Height: 9'

## Other Views:



Side View



Front View



Back View

## Performance Table: DLS6-MCT-BN

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
DLS6-MCT-BN	15W	120V	1000LM	3000K/ 4000K/ 5000K	B1-U2-G1	67

## Sample Ordering

Model Color Temp. Color

DLS6 - MCT - BN

## Factory-Installed Options:

Blank = No Option For Accessories  
OPT-EM-DLS6 = MOUNT IN EXTENDED BASE

## Example:

- DLS6-MCT-BN (FOR DSL6 15W FIXTURE 120V)
- DLS6-MCT-BN OPT-EM-DLS6 (FOR DSL6 15W FIXTURE 120V) (MOUNT IN EXTENDED BASE)

## MOUNTING KIT and OPTION:



Recessed Mounting Kit included



OPT-EM-DLS6  
7-1/4" x 1-1/2"

## Other Model:



DLS6-MCT-PIR  
with PIR Motion Sensor



DLS6-MCT-277V  
277V Disk Light

